

INDUSTRIAL COMPONENT DATA

VS-PSC 1,5/5-M PE 1689323 PHOENIX CONTACT Contact insert

Brand: PHOENIX CONTACT | Manufacturer Part Number: VS-PSC 1,5/5-M PE



Manufacturer	PHOENIX CONTACT
MPN / Reference	VS-PSC 1,5/5-M PE
Catalog number	1689323
Category	D-Sub connector
Minimum order	10 Pcs
Document ID	EO-64E5BBE686
Generated	2026-09-22

Product Overview

Contact insert

POWER-SUBCON base housing, for the recessed side, 5 poles, with PE advance contact, shielded, color: Green

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Key Commercial Data

Orderkey 1689323

Packing unit 10 pc

Minimum order quantity 10 pc

Note Made to Order (non-returnable)

Catalog page Page 215 (C-2-2013)

GTIN 4017918893170

Weight per Piece (excluding packing) 8.110 g

Custom tariff number 85366990

Country of origin PL (Poland)

Mechanical characteristics

Number of positions 5

Insertion/withdrawal cycles >= 100

Connection method Printed circuit connection

Conductor cross section 0.14 mm² ... 1.5 mm²

Connection cross section AWG 28 ... 16

Mounting type Threads

Insulation resistance 1 T?

Type 15

Size of housing 2

Type of note Notes on operation

Note Only actuate MINI COMBICON connectors when under no load condition. If for operating reasons small loads must be switched, experimental values are available upon request.

Ambient conditions

Ambient temperature (operation) -20 °C ... 80 °C

Material data

Flammability rating according to UL 94 V0

Contact carrier material PA

Contact material Copper alloy

Contact surface material Tin-plated

Height 13.7 mm

Electrical characteristics

Number of positions 5

Rated current 8 A

Overvoltage category III

Degree of pollution 3

Rated voltage (III/3) 250 V

Standards and Regulations

Flammability rating according to UL 94 V0

Environmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

Classifications

eCl@ss 4.027140816eCl@ss 4.127260701eCl@ss 5.027260701eCl@ss 5.127261200eCl@ss 6.027261200eCl@ss 7.027440205eCl@ss 8.027...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / VS-PSC 1,5/5-M PE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.