

INDUSTRIAL COMPONENT DATA

QUINT-PS/1AC/24DC/10/CO 2320911 PHOENIX CONTACT

Power supply, with protective coating

Brand: PHOENIX CONTACT | Manufacturer Part Number: QUINT-PS/1AC/24DC/10/CO



Manufacturer	PHOENIX CONTACT
MPN / Reference	QUINT-PS/1AC/24DC/10/CO
Catalog number	2320911
Category	DC-power supply
Minimum order	1 Pcs
Document ID	EO-EF9787B66D
Generated	2026-09-22

Product Overview

Power supply, with protective coating

Primary Switching Power Supplies, QUINT POWER, Screw Connection, Rail Mounting, SFB Technology (Selective Fuse Breaking), Input:1Phase, Output: 24 VDC / 10 A

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Power Supplies (PS)

Additional Product Information

Key Commercial Data

Orderkey 2320911

Packing unit 1 pc

Catalog page Page 217 (C-4-2017)

GTIN 4046356520027

Weight per Piece (excluding packing) 1,100.000 g

Custom tariff number 85044030

Country of origin TH (Thailand)

Dimensions

Width 60 mm

Height 130 mm

Depth 125 mm

Width with alternative assembly 122 mm

Height with alternative assembly 130 mm

Depth with alternative assembly 63 mm

Ambient conditions

Degree of protection IP20

Ambient temperature (operation) -40 °C ... 70 °C (> 60 °C Derating: 2.5 %/K)

Ambient temperature (storage/transport) -40 °C ... 85 °C

Max. permissible relative humidity (operation) 100 % (at 25 °C, non-condensing)

Climatic class 3K3 (in acc. with EN 60721)

Degree of pollution 2

Installation height 5000 m

Input data

Nominal input voltage range 100 V AC ... 240 V AC

110 V DC ... 250 V DC

Input voltage range 85 V AC ... 264 V AC

90 V DC ... 410 V DC +5 % (UL 508: ≤ 250 V DC)

Dielectric strength maximum 300 V AC

AC frequency range 45 Hz ... 65 Hz

Frequency range DC 0 Hz

Discharge current to PE < 3.5 mA

Current consumption 2.2 A (120 V AC)

1.3 A (230 V AC)

2.5 A (110 V DC)

1.2 A (220 V DC)

Nominal power consumption 303 VA

Inrush surge current < 15 A

Mains buffering typ. 36 ms (120 V AC)

typ. 36 ms (230 V AC)

Input fuse 10 A (slow-blow, internal)

Choice of suitable circuit breakers 10 A ... 20 A (AC: Characteristics B, C, D, K)

Type of protection Transient surge protection

Protective circuit/component Varistor, gas-filled surge arrester

Output data

Nominal ou...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / QUINT-PS/1AC/24DC/10/CO with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.