

INDUSTRIAL COMPONENT DATA

STEP-PS/ 1AC/ 5DC/6.5 2868541 PHOENIX CONTACT Power supply unit

Brand: PHOENIX CONTACT | Manufacturer Part Number: STEP-PS/ 1AC/ 5DC/6.5



Manufacturer	PHOENIX CONTACT
MPN / Reference	STEP-PS/ 1AC/ 5DC/6.5
Catalog number	2868541
Category	DC-power supply
Minimum order	1 Pcs
Document ID	EO-A2A8CAF95B
Generated	2026-09-22

Product Overview

Power supply unit

STEP POWER primary switch-mode power supply for rail mounting, input: single-phase, output: 5 V DC/6.5 A

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Power Supplies (PS)
--------------	---------------------------------------

Additional Product Information

Key Commercial Data

Orderkey 2868541

Packing unit 1 pc

Catalog page Page 243 (C-4-2017)

GTIN 4046356309592

Weight per Piece (excluding packing) 276.000 g

Custom tariff number 85044030

Country of origin PL (Poland)

Dimensions

Width 72 mm

Height 90 mm

Depth 61 mm

Ambient conditions

Degree of protection IP20

Ambient temperature (operation) -25 °C ... 70 °C (> 55° C derating : 2.5%/K)
Ambient temperature (storage/transport) -40 °C ... 85 °C
Max. permissible relative humidity (operation) ≤ 95 % (at 25 °C, non-condensing)
Climatic class 3K3 (in acc. with EN 60721)
Degree of pollution 2
Input data
Nominal input voltage range 100 V AC ... 240 V AC
Input voltage range 85 V AC ... 264 V AC
95 V DC ... 250 V DC
AC frequency range 45 Hz ... 65 Hz
Frequency range DC 0 Hz
Current consumption 0.5 A (120 V AC)
0.3 A (230 V AC)
Nominal power consumption 72.1 VA
Inrush surge current < 15 A (typical)
Mains buffering typ. 25 ms (120 V AC)
typ. 140 ms (230 V AC)
Input fuse 3.15 A (slow-blow, internal)
Choice of suitable circuit breakers 6 A ... 16 A (Characteristics B, C, D, K)
Power factor (cos phi) 0.57
Type of protection Transient surge protection
Protective circuit/component Varistor
Output data
Nominal output voltage 5 V DC ±1 %
Setting range of the output voltage (USet) 4 V DC ... 6.5 V DC (> 5 V DC, constant capacity restricted)
Nominal output current (IN) 6.5 A (-25 °C ... 55 °C)
7.1 A (-25°C ... 40°C permanent)
Output current I_{max} 11.5 A
Derating 55 °C ... 70 °C (2.5%/K)
Connection in....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / STEP-PS/ 1AC/ 5DC/6.5 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.