

INDUSTRIAL COMPONENT DATA

TRIO-PS/3AC/24DC/40 2866404 PHOENIX CONTACT Power supply unit

Brand: PHOENIX CONTACT | Manufacturer Part Number: TRIO-PS/3AC/24DC/40



Manufacturer	PHOENIX CONTACT
MPN / Reference	TRIO-PS/3AC/24DC/40
Catalog number	2866404
Category	DC-power supply
Minimum order	1 Pcs
Document ID	EO-2D4C8CDF51
Generated	2026-09-22

Product Overview

Power supply unit

TRIO POWER primary switched power supply for rail mounting, input: three-phase, output: 24 V DC/40 A

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Power Supplies (PS)

Additional Product Information

Key Commercial Data

Orderkey 2866404

Packing unit 1 pc

Catalog page Page 171 (C-6-2015)

GTIN 4046356046688

Weight per Piece (excluding packing) 2,900.000 g

Custom tariff number 85044030

Country of origin CN (China)

Dimensions

Width 139 mm

Height 130 mm

Depth 190 mm

Ambient conditions

Degree of protection IP20

Ambient temperature (operation) -25 °C ... 70 °C (> 55° C derating : 2.5%/K)
Ambient temperature (storage/transport) -40 °C ... 85 °C
Max. permissible relative humidity (operation) 95 % (at 25 °C, non-condensing)
Climatic class 3K3 (in acc. with EN 60721)
Degree of pollution 2
Input data
Nominal input voltage range 3x 400 V AC ... 500 V AC
Input voltage range 3x 320 V AC ... 575 V AC
2x 360 V AC ... 575 V AC (for 2-phase operation)
AC frequency range 45 Hz ... 65 Hz
Discharge current to PE < 3.5 mA
Current consumption 3x 2 A (400 V AC)
3x 1.6 A (480 V AC)
Nominal power consumption 1387 VA
Inrush surge current < 20 A
Mains buffering > 16 ms (400 V AC)
> 20 ms (480 V AC)
Choice of suitable circuit breakers 6 A ... 16 A (Characteristics B, C, D, K)
Power factor (cos phi) 0.76
Type of protection Transient surge protection
Protective circuit/component Varistor
Output data
Nominal output voltage 24 V DC ± 1 %
Setting range of the output voltage (USet) 22.5 V DC ... 29.5 V DC (> 24 V DC, constant capacity restricted)
Nominal output current (IN) 40 A (-25 °C ... 55 °C)
Derating 55 °C ... 70 °C (2.5%/K)
Connection in parallel Yes, for redundancy and increased capacity
Connection....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / TRIO-PS/3AC/24DC/40 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.