INDUSTRIAL COMPONENT DATA

RIF-1-RPT-LV-120AC/2X21AU 2903328 PHOENIX CONTACT Relay Module

Brand: PHOENIX CONTACT | Manufacturer Part Number: RIF-1-RPT-LV-120AC/2X21AU



Manufacturer	PHOENIX CONTACT
MPN / Reference	RIF-1-RPT-LV-120AC/2X21AU
Catalog number	2903328
Category	Switching relay
Minimum order	10 Pcs
Document ID	EO-456BE16533
Generated	2026-11-18

Product Overview

Relay Module
Pre-assembled relay module with push-in connection, consisting of: relay socket, relay with multi-layer universal contact, plug-in indication/anti-parasitic module and clamping flange. Contact type: 2 investor contacts. Input voltage: 120 V AC

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Relays

Additional Product Information

Key Commercial Data
Orderkey 2903328
Packing unit 10 pc
Minimum order quantity 10 pc
Catalog page Page 341 (C-5-2017)
GTIN 4046356732321
Weight per Piece (excluding packing) 68.100 g
Custom tariff number 85364900
Country of origin DE (Germany)
Note
Utilization restriction EMC: class A product, see manufacturer's declaration in the download area
Type of note Notes on operation
Note FBS 2-6... plug-in bridge for the input side (A2) and FBS-2-8... plug-in bridge for the output side (11/21)

Dimensions
Width 16 mm
Height 93 mm
Depth 75 mm
Ambient conditions
Ambient temperature (operation) -40 °C ... 50 °C
Ambient temperature (storage/transport) -40 °C ... 85 °C
Coil side
Nominal input voltage UN 120 V AC
Input voltage range in reference to UN see diagram
Mains frequency 50/60 Hz
Typical input current at UN 8 mA
Typical response time 3 ms ... 12 ms
Typical release time range 3 ms ... 20 ms
Coil voltage 120 V AC
Protective circuit Varistor
Operating voltage display Yellow LED
Power dissipation for nominal condition 0.96 W
Contact side
Contact type 2 PDT
Type of switch contact Single contact
Contact material AgNi, hard gold-plated
Maximum switching voltage 30 V AC
36 V DC
Minimum switching voltage 100 mV (at 10 mA)
Min. switching current 1 mA (at 24 V)
Maximum inrush current 50 mA
Limiting continuous current 50 mA
Interrupting rating (ohmic load) max. 1.2 W (at 24 V DC)
Contact side (with destroyed gold layer)
Contact material AgNi
Note the following values are applicable if a gold....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / RIF-1-RPT-LV-120AC/2X21AU with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES
Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.