INDUSTRIAL COMPONENT DATA

RIF-1-RPT-LV-230AC/2X21MS 2905292 PHOENIX CONTACT Relay Module

Brand: PHOENIX CONTACT | Manufacturer Part Number: RIF-1-RPT-LV-230AC/2X21MS



Manufacturer	PHOENIX CONTACT
MPN / Reference	RIF-1-RPT-LV-230AC/2X21MS
Catalog number	2905292
Category	Switching relay
Minimum order	10 Pcs
Document ID	EO-8DEAFB4696
Generated	2026-11-18

Product Overview

Relay Module
Pre-assembled relay module with push-in connection, consisting of: relay socket, relay fixing brackets, plug-in anti-parasitic module and relay with power contact with test button and integrated status LED. Type of contact: 2investor contacts. Input voltage: 230VAC

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Relays

Additional Product Information

Key Commercial Data
Orderkey 2905292
Packing unit 10 pc
Catalog page Page 345 (C-5-2017)
GTIN 4046356945387
Weight per Piece (excluding packing) 70.320 g
Custom tariff number 85364900
Country of origin CN (China)
Note
Utilization restriction EMC: class A product, see manufacturer's declaration in the download area
Dimensions
Width 16 mm

Height 93 mm
Depth 75 mm
Ambient conditions
Ambient temperature (operation) -40 °C ... 45 °C
Ambient temperature (storage/transport) -40 °C ... 85 °C
Coil side
Nominal input voltage UN 230 V AC (50/60 Hz)
Input voltage range in reference to UN see diagram
Mains frequency 50/60 Hz
Typical input current at UN 3.5 mA
Typical response time 4 ms ... 10 ms
Typical release time range 3 ms ... 20 ms
Coil voltage 230 V AC
Protective circuit Varistor
Operating voltage display Yellow LED
Power dissipation for nominal condition 0.81 W
Contact side
Contact type 2 PDT
Type of switch contact Single contact
Contact material AgNi
Maximum switching voltage 250 V AC/DC
Minimum switching voltage 12 V (at 10 mA)
Min. switching current 10 mA (at 12 V)
Maximum inrush current 16 A (20 ms, N/O contact)
Limiting continuous current see diagram
Interrupting rating (ohmic load) max. 192 W (at 24 V DC)
62 W (at 48 V DC)
42 W (at 60 V DC)
55 W (at 110 V DC)
66 W (at 220 V DC)
2000 VA (for 250 V AC)
Switching capacity min. 120 mW
Switching capacity 1 A (at 24 V, DC13)
1.5 A (at 230 V, AC15)
Connection data 1
Connection name Coil side
Connection method Push-in connection
Str...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / RIF-1-RPT-LV-230AC/2X21MS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.