INDUSTRIAL COMPONENT DATA

RIF-3-RPT-LDP-24DC/3X21 2903294 PHOENIX CONTACT Relay Module

Brand: PHOENIX CONTACT | Manufacturer Part Number: RIF-3-RPT-LDP-24DC/3X21



Manufacturer	PHOENIX CONTACT
MPN / Reference	RIF-3-RPT-LDP-24DC/3X21
Catalog number	2903294
Category	Switching relay
Minimum order	5 Pcs
Document ID	EO-8B8C650520
Generated	2026-11-19

Product Overview

Relay Module
Pre-assembled relay module with push-in connection, consisting of: relay socket, relay with power contact and clamping flange. Contact type: 3 investor contacts. Input voltage: 24 V DC

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Relays

Additional Product Information

Key Commercial Data
Orderkey 2903294
Packing unit 5 pc
Catalog page Page 355 (C-5-2017)
GTIN 4046356732710
Weight per Piece (excluding packing) 173.290 g
Custom tariff number 85364110
Country of origin DE (Germany)
Note
Utilization restriction EMC: class A product, see manufacturer's declaration in the download area
Dimensions
Width 40 mm
Height 103 mm

Depth 90 mm
Ambient conditions
Ambient temperature (operation) -40 °C ... 60 °C
Ambient temperature (storage/transport) -40 °C ... 85 °C
Coil side
Nominal input voltage UN 24 V DC
Input voltage range in reference to UN see diagram
Typical input current at UN 60 mA
Typical response time 18 ms
Typical release time 20 ms
Coil voltage 24 V DC
Protective circuit Damping diode
Operating voltage display Yellow LED
Power dissipation for nominal condition 1.44 W
Contact side
Contact type 3 PDTs
Type of switch contact Single contact
Contact material AgNi
Maximum switching voltage 250 V AC/DC
Minimum switching voltage 10 V (At 24 mA)
Min. switching current 10 mA (at 24 V)
Maximum inrush current 30 A (20 ms, N/O contact)
Limiting continuous current 8.5 A (see diagram)
Interrupting rating (ohmic load) max. 204 W (at 24 V DC)
124 W (at 48 V DC)
108 W (at 60 V DC)
52 W (at 110 V DC)
48 W (at 220 V DC)
2125 VA (for 250 V AC)
Switching capacity 2 A (at 24 V, DC13)
0.22 A (at 120 V, DC13)
0.11 A (at 250 V, DC13)
3 A (at 24 V, AC15)
3 A (at 120 V, AC15)
1.5 A (at 240 V, AC15)
Connection data 1
Connection name Coil side
Connection method Push-in....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / RIF-3-RPT-LDP-24DC/3X21 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.