

INDUSTRIAL COMPONENT DATA

STEP-PS/ 1AC/ 5DC/2 2320513 PHOENIX CONTACT Power supply unit

Brand: PHOENIX CONTACT | Manufacturer Part Number: STEP-PS/ 1AC/ 5DC/2



Manufacturer	PHOENIX CONTACT
MPN / Reference	STEP-PS/ 1AC/ 5DC/2
Catalog number	2320513
Category	DC-power supply
Minimum order	1 Pcs
Document ID	EO-58574FA157
Generated	2026-09-21

Product Overview

Power supply unit

STEP POWER Primary Switch-On Power Power Supply for Rail Mounting, Input: Single Phase, Output: 5 V DC/2 A

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > Power Supplies (PS)**

Additional Product Information

Key Commercial Data

Orderkey 2320513

Packing unit 1 pc

Catalog page Page 242 (C-4-2017)

GTIN 4046356674744

Weight per Piece (excluding packing) 86.000 g

Custom tariff number 85044030

Country of origin PL (Poland)

Dimensions

Width 18 mm

Height 90 mm

Depth 61 mm

Ambient conditions

Degree of protection IP20

Ambient temperature (operation) -25 °C ... 70 °C (> 55° C derating : 2.5%/K)
Ambient temperature (storage/transport) -40 °C ... 85 °C
Max. permissible relative humidity (operation) ≤ 95 % (at 25 °C, non-condensing)
Climatic class 3K3 (in acc. with EN 60721)
Degree of pollution 2
Input data
Nominal input voltage range 100 V AC ... 240 V AC
Input voltage range 85 V AC ... 264 V AC
95 V DC ... 250 V DC
AC frequency range 45 Hz ... 65 Hz
Frequency range DC 0 Hz
Current consumption 0.2 A (120 V AC)
0.13 A (230 V AC)
Nominal power consumption 28.9 VA
Inrush surge current < 15 A
Mains buffering typ. 25 ms (120 V AC)
typ. 110 ms (230 V AC)
Input fuse 1.25 A (slow-blow, internal)
Choice of suitable circuit breakers 6 A ... 16 A (AC: Characteristics B, C, D, K)
Power factor (cos phi) 0.44
Output data
Nominal output voltage 5 V DC ±1 %
Nominal output current (IN) 2 A (-25°C ... 40°C permanent)
2.2 A (-25 °C ... 55 °C)
Output current I_{max} 3.7 A
Derating 55 °C ... 70 °C (2.5%/K)
Connection in parallel Yes, for redundancy and increased capacity
Connection in series yes
Output overvoltage protection < 10 V DC
Residual ripple < 50 mVPP
Output power 10 W
Typical response time < 0.5 s
Maximu...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / STEP-PS/ 1AC/ 5DC/2 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.