

INDUSTRIAL COMPONENT DATA

UNO-PS/1AC/24DC/ 30W 2902991 PHOENIX CONTACT Power supply unit

Brand: PHOENIX CONTACT | Manufacturer Part Number: UNO-PS/1AC/24DC/ 30W



Manufacturer	PHOENIX CONTACT
MPN / Reference	UNO-PS/1AC/24DC/ 30W
Catalog number	2902991
Category	DC-power supply
Minimum order	1 Pcs
Document ID	EO-768300690D
Generated	2026-09-22

Product Overview

Power supply unit

UNO POWER primary switching power supply for rail mounting, input: single-phase, output: 24 V DC/30 W

UNO POWER primary metered power supply for DIN rail mounting, input: 1-phase, output: 24 V DC / 30 W

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > Power Supplies (PS)**

Additional Product Information

Key Commercial Data

Orderkey 2902991

Packing unit 1 pc

Catalog page Page 226 (C-4-2017)

GTIN 4046356729192

Weight per Piece (excluding packing) 150.000 g

Custom tariff number 85044030

Country of origin PL (Poland)

Dimensions

Width 22.5 mm

Height 90 mm

Depth 84 mm

Ambient conditions

Degree of protection IP20

Ambient temperature (operation) -25 °C ... 70 °C (> 55 °C Derating: 2.5 %/K)

Ambient temperature (start-up type tested) -40 °C

Ambient temperature (storage/transport) -40 °C ... 85 °C

Max. permissible relative humidity (operation) ≤ 95 % (at 25 °C, non-condensing)

Climatic class 3K3 (in acc. with EN 60721)

Degree of pollution 2

Input data

Nominal input voltage range 100 V AC ... 240 V AC

Input voltage range 85 V AC ... 264 V AC

Current consumption 0.8 A (100 V AC)

0.4 A (240 V AC)

Nominal power consumption 72.1 VA

Inrush surge current < 20 A (typical)

Mains buffering typ. 25 ms (120 V AC)

typ. 115 ms (230 V AC)

Input fuse 2 A (slow-blow, internal)

Choice of suitable circuit breakers 6 A ... 16 A (Characteristics B, C, D, K)

Power factor (cos phi) 0.47

Type of protection Transient surge protection

Protective circuit/component Varistor

Output data

Nominal output voltage 24 V DC ±1 %

Nominal output current (IN) 1.25 A (-25 °C ... 55 °C)

Derating 55 °C ... 70 °C (2.5%/K)

Connection in parallel Yes, for redundancy and increased capacity

Connection in series yes

Feedback resistance < 35 V DC

Output overvoltage protection ≤ 35 V DC

Control deviation < 1 % (change in load, static...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UNO-PS/1AC/24DC/ 30W with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.