INDUSTRIAL COMPONENT DATA

VS-OE-IP20-93R-LI/2,0 1416236 PHOENIX CONTACT Network cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: VS-OE-IP20-93R-LI/2,0



Manufacturer	PHOENIX CONTACT
MPN / Reference	VS-OE-IP20-93R-LI/2,0
Catalog number	1416236
Category	Sensor-actuator patch cord
Minimum order	1 Pcs
Document ID	EO-623B30EA82
Generated	2026-11-18

Product Overview

Network cable
Ready-made PROFINET cable, CAT 5e, shielded, star quads, flexible AWG 22 (19 wires), RAL 6018 (yellow green), free cable end in RJ45/IP20 connector, Line, length: 2 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Key Commercial Data
Orderkey 1416236
Packing unit 1 pc
Note Made to Order (non-returnable)
Catalog page Page 310 (PC-2011)
GTIN 4046356472463
Weight per Piece (excluding packing) 142.700 g
Custom tariff number 85444210
Country of origin PL (Poland)
Ambient conditions
Degree of protection IP20
General data
Number of positions 4

Cable
Cable type PROFINET robot CAT5
Cable type (abbreviation) 93R
UL AWM style 20233 (80°C/300 V)
Signal type/category PROFINET CAT5 (IEC 11801), 100 Mbps
EtherCAT®CAT5 (IEC 11801), 100 Mbps
Cable structure 1x4xAWG22/19; S/TQ
Conductor cross section 4x 0.34 mm²
AWG signal line 22
Conductor structure signal line 19x 0.15 mm
Core diameter including insulation 1.5 mm
Wire colors White, yellow, blue, orange
Overall twist Star quad
Shielding Tinned copper braided shield
Optical shield covering 85 %
External sheath, color green RAL 6018
Outer sheath thickness approx. 1 mm
External cable diameter D 6.5 mm ±0.2 mm
Minimum bending radius, fixed installation 5 x D
Torsion force ± 180 °/m (1 000 000 torsion cycles)
Cable weight 55 kg/km
Outer sheath, material PUR
Material conductor insulation Foamed PE
Conductor material Tin-plated Cu litz wires
Insulation resistance >= 500 M?*km
Loop resistance <= 120.00 ?/km
Wave impedance 100 ? ±5 ? (at 100 MHz)
Attenuation 2.9 dB (with 1 MHz)
5 dB (at 4 ?Hz)
8.1 dB (at 10 MHz)
10.4 dB (at 16 MHz)
11.9 dB (at 20 ?Hz)
15.5 dB (at 31.25 ?Hz)
26.5 dB (at 62.5 ?Hz)
41 dB (at 100 MHz)
Signal runtime 4.8 ns/m
Nominal voltage, cable 3...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / VS-OE-IP20-93R-LI/2,0 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.