INDUSTRIAL COMPONENT DATA

# US-PML-P100 (D100) 1014218 PHOENIX CONTACT Prohibition sign

**Brand: PHOENIX CONTACT | Manufacturer Part Number: US-PML-P100 (D100)**



| | |
|---|---|
| Manufacturer | PHOENIX CONTACT |
| MPN / Reference | US-PML-P100 (D100) |
| Catalog number | 1014218 |
| Category | Warning/signing plate |
| Minimum order | 10 Pcs |
| Document ID | EO-BF20FBE23E |
| Generated | 2026-11-19 |

## Product Overview

Prohibition sign
Prohibition sign, Card, red/white, pre-printed, labelable with: BLUEMARKIDCOLOR, BLUEMARKID, THERMOMARK PRIME, THERMOMARK CARD 2.0, THERMOMARK CARD, mounting class: glued, diameter: 100 mm, usable surface: d: 100 mm, Number of individual indexes: 1
Prohibition sign, Card, red/white, pre-printed, can be labeled with: BLUEMARK ID COLOR, BLUEMARK ID, THERMOMARK PRIME, THERMOMARK CARD 2.0, THERMOMARK CARD: Diagonal bar, mounting type: adhesive, diameter: 100 mm, Number of individual labels: 1, text field height: 100 mm, text field width: 100 mm

STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

| | |
|---|---|
| Catalog path | PHOENIX CONTACT > MS Material |

## Additional Product Information

Technical dataProduct propertiesProduct type Prohibition sign unprinted
Area of application Prohibition signs
Prohibition marking according to ISO 7010
Type circular
Data management status
Article revision 02
Marking
Number of individual labels 1
Number of individual labels per row 1

Printing Diagonal bar
Identification technology Thermal transfer
DimensionsWidth 100 mm
Text field width 100.00 mm
Height 100 mm
Text field height 100.00 mm
Depth 0.09 mm
Diameter 100.00 mm
Min. material thickness 0.09 mm
Material specificationsColor multicolored
red (RAL 3001)
white (RAL 9010)
Material PVC
Components Silicone-free
Environmental and real-life conditionsAmbient conditions
Ambient temperature (operation) -40 °C ... 90 °C
Ambient temperature (assembly) > 10 °C
Recommended ambient temperature (storage/transport) 22 °C
Recommended humidity (storage/transport) 50 % ... 55 % (Storage in a dry and dark place in the original packaging is recommended)
Shelf life 2 years
Standards and regulationsWipe resistance DIN EN 61010-1 (VDE 0411-1)
MountingMounting type adhesive

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / US-PML-P100 (D100) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.