INDUSTRIAL COMPONENT DATA

PSL 1436966 PHOENIX CONTACT Lock, depth: 63.8 mm, width: 9.7 mm, height: 8.7 mm, number of poles: 2, color: ..

Brand: PHOENIX CONTACT | Manufacturer Part Number: PSL



Manufacturer	PHOENIX CONTACT
MPN / Reference	PSL
Catalog number	1436966
Category	Installation clamp for meters
Minimum order	50 Pcs
Document ID	EO-CF1DFE008A
Generated	2026-11-19

Product Overview

Lock, depth: 63.8 mm, width: 9.7 mm, height: 8.7 mm, number of poles: 2, color: orange

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Modular TBs

Additional Product Information

Technical dataProduct propertiesProduct type Plug
Number of positions 2
DimensionsWidth 9.7 mm
Height 8.7 mm
Depth 63.8 mm
Material specificationsColor orange
Static insulating material application in cold -60 °C
Relative insulation material temperature index (Elec., UL 746 B) 130 °C
Fire protection for rail vehicles (DIN EN 45545-2) R22 HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R23 HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R24 HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R26 HL 1 - HL 3
Surface flammability NFPA 130 (ASTM E 162) passed
Specific optical density of smoke NFPA 130 (ASTM E 662) passed
Smoke gas toxicity NFPA 130 (SMP 800C) passed

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PSL with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.