INDUSTRIAL COMPONENT DATA

PST 1,3/ 4-5,0 L18 1990504 PHOENIX CONTACT Pin strip

Brand: PHOENIX CONTACT | Manufacturer Part Number: PST 1,3/ 4-5,0 L18



Manufacturer	PHOENIX CONTACT
MPN / Reference	PST 1,3/ 4-5,0 L18
Catalog number	1990504
Category	Printed circuit board connector
Minimum order	250 Pcs
Document ID	EO-22667F4050
Generated	2026-11-19

Product Overview

Pin strip
Male connector, nominal section: 1.5 mm², color: black, nominal current: 12 A (Depending on the connector used), nominal voltage (III/2): 320 V, contact surface: Tin, contact type: Male, number of potentials: 4, number of rows: 1, number of poles: 4, number of connections: 4, article family: PST 1.3/.. -V, pitch: 5 mm, mounting: Solder THR, pin arrangement: Linear pin arrangement, pin length [P]: 3.5 mm, plug-in system: COMBICON PST 1.3, locking: without, fixing type: without, packaging type: boxed, The maximum current depends on the connector used. Of the two current values, the lower value for the connector and the male connector is decisive. The plug is made of high-temperature resistant plastic, making it suitable for the reflow soldering process.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Key Commercial Data
Orderkey 1990504
Packing unit 250 pc
Minimum order quantity 250 pc
GTIN 4017918958015
Weight per Piece (excluding packing) 0.900 g
Custom tariff number 85366930
Country of origin DE (Germany)
Dimensions

Width 20 mm
Pitch 5 mm
Dimension a 15 mm
Width [w] 20 mm
Height [h] 18 mm
Height 9.5 mm
Length of the solder pin 3.5 mm
Pin dimensions ø 1.3 mm
General
Range of articles PST 1,3/..-V
Rated voltage (III/3) 250 V
Connection in acc. with standard EN-VDE
Nominal current IN 12 A
Color black
Number of positions 4
Standards and Regulations
Connection in acc. with standard EN-VDE
CUL
Environmental Product Compliance
China RoHS Environmentally friendly use period: unlimited = EFUP-e
No hazardous substances above threshold values
Classifications
eCl@ss 4.0272607xxeCl@ss 4.127260701eCl@ss 5.027260701eCl@ss 5.127260700eCl@ss 6.027260700eCl@ss 7.027440402eCl@ss 8.027440402eCl@ss 9.027440402
ETIM 3.0EC001121ETIM 4.0EC002637ETIM 5.0EC002637ETIM 6.0EC002637
UNSPSC 6.0130211801UNSPSC 7.090139121432UNSPSC 1134131203UNSPSC 12.0139121432UNSPSC 13.239121409

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PST 1,3/ 4-5,0 L18 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES
Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.