INDUSTRIAL COMPONENT DATA

RC-17P1N8A2K00 1601474 PHOENIX CONTACT Device connector, front mounting

Brand: PHOENIX CONTACT | Manufacturer Part Number: RC-17P1N8A2K00



Manufacturer	PHOENIX CONTACT
MPN / Reference	RC-17P1N8A2K00
Catalog number	1601474
Category	Circular connector, mounting (without cable)
Minimum order	40 Pcs
Document ID	EO-4746CD6711
Generated	2026-11-19

Product Overview

Device connector, front mounting
M23, Conect. plug. to be apar. front wall, RC, straight, shielded: yes, Screw lock, No. of poles: 17, Direction of rotation: Standard, contact type: Male, Crimped connection, Flat joint, 4x Ø2.7, flange measurement: 25 mm x 25 mm, coding:N
M23, Device connector front mounting, series: RC, straight, shielded: yes, Screw locking mechanism, No. of pos.: 17, Direction of rotation: Standard, contact connection type: Pin, Crimp connection, Flat gasket, 4x Ø 2.7 mm, flange dimensions: 25 mm x 25 mm, coding: N

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Technical dataNotesOrder information: Order crimp contacts Ø 1 mm separately
Product propertiesProduct type Circular connectors (device side)
ConnectorInsulating body
Note Order information: Order crimp contacts Ø 1 mm separately
Coding N
Connection method Crimp connection
Contact switching type Pin
Application Signal
Number of positions 17
Direction of rotation Standard

Connection profile 17
Contact diameterPower contacts 1 mm
Rated currentPower contacts 8 A
Rated voltage 48 V AC
74 V DC
Rated surge voltage 1.5 kV
Overvoltage category III
Degree of pollution 3
Housing
Order information: Order contact inserts separately
Housing material GD-Zn
Flange dimensions 25 mm x 25 mm
Type of locking Screw locking mechanism
Pg screw connection none
Degree of protection (plugged in) IP67
Thread type M23
Environmental and real-life conditionsAmbient conditions
Ambient temperature (storage/transport) 15 °C ... 25 °C
Permissible humidity (storage/transport) 50 % ... 65 %

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / RC-17P1N8A2K00 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.