


## INDUSTRIAL COMPONENT DATA

# PT 1,5/10-5,0-H BK 1989528 PHOENIX CONTACT PCB terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: PT 1,5/10-5,0-H BK



|                 |                                |
|-----------------|--------------------------------|
| Manufacturer    | PHOENIX CONTACT                |
| MPN / Reference | PT 1,5/10-5,0-H BK             |
| Catalog number  | 1989528                        |
| Category        | Printed circuit board terminal |
| Minimum order   | 100 Pcs                        |
| Document ID     | EO-3C209CCA9C                  |
| Generated       | 2026-09-29                     |

## Product Overview

### PCB terminal block

Terminal block for printed circuit board, nominal current: 17.5 A, nominal voltage (III/2): 400 V, nominal section: 1.5 mm<sup>2</sup>, number of potentials: 10, number of rows: 1, number of poles per row: 10, article family: PT 1.5/.. -H, pitch: 5 mm, connection type: Screw connection with wire protection bracket, mounting: Wave soldering, conductor connection direction/printed circuit board: 0 °, color: black, Pin arrangement: Linear pin arrangement, Pin length [P]: 3.5 mm, number of solder pins per potential: 1, packaging type: boxed

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                        |
|--------------|----------------------------------------|
| Catalog path | PHOENIX CONTACT > PCB Connectors (PCC) |
|--------------|----------------------------------------|

## Additional Product Information

### Key Commercial Data

Orderkey 1989528

Packing unit 100 pc

Minimum order quantity 100 pc

Note Made to Order (non-returnable)

GTIN 4017918944360

Weight per Piece (excluding packing) 9.490 g

Custom tariff number 85369010

Country of origin DE (Germany)

Dimensions

Length [ l ] 9 mm

Pitch 5 mm

Dimension a 45 mm

Height 11.4 mm

Height [ h ] 11.3 mm

Solder pin [P] 3.5 mm

Pin spacing 5 mm

Hole diameter 1.3 mm

General

Range of articles PT 1,5/..-H

Insulating material group I

Rated surge voltage (III/3) 4 kV

Rated surge voltage (III/2) 4 kV

Rated surge voltage (II/2) 4 kV

Rated voltage (III/3) 250 V

Rated voltage (III/2) 400 V

Rated voltage (II/2) 630 V

Connection in acc. with standard EN-VDE

Nominal current I<sub>N</sub> 17.5 A

Nominal cross section 1.5 mm<sup>2</sup>

Maximum load current 17.5 A

Insulating material PA

Solder pin surface

Flammability rating according to UL 94 V0

Internal cylindrical gage A1

Stripping length 5 mm

Number of positions 10

Screw thread M2,6

Tightening torque, min 0.35 Nm

Tightening torque max 0.4 Nm

Connection data

Conductor cross section AWG min. 26

Conductor cross section AWG max. 14

2 conductors with same cross section, solid min. 0.2 mm<sup>2</sup>

2 conductors with same cross section, solid max. 0.75 mm<sup>2</sup>

2 conductors with same cross section, stranded min. 0.2 mm<sup>2</sup>

2 conductors with same cross section, stranded max. 0.75 mm<sup>2</sup>

2 conductors with same cross section, stranded, ferrules without plastic sleeve, min. 0.25 mm<sup>2</sup>

2 conductors with same cross section, stranded, ferrules without plasti...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PT 1,5/10-5,0-H BK with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.