

INDUSTRIAL COMPONENT DATA

MKDSFW 1,5/ 7 BD:1,2,23-27 1706907 PHOENIX CONTACT

Terminal block for printed circuit board, nominal current..

Brand: PHOENIX CONTACT | Manufacturer Part Number: MKDSFW 1,5/ 7 BD:1,2,23-27

PRODUCT IMAGE\nNOT
AVAILABLE

Manufacturer	PHOENIX CONTACT
MPN / Reference	MKDSFW 1,5/ 7 BD:1,2,23-27
Catalog number	1706907
Category	Printed circuit board terminal
Minimum order	50 Pcs
Document ID	EO-5ED33FF8E3
Generated	2026-09-28

Product Overview

Terminal block for printed circuit board, nominal current: 17.5 A, nominal voltage: 400 V, pitch: 5 mm, number of poles: 7, connection type: Screw connection with traction capsule, mounting: Wave soldering, driver/printed circuit board connection direction: 90 °, color: green

Terminal block for printed circuit board, nominal current: 17.5 A, dimensioning voltage (III/2): 400 V, nominal section: 1.5 mm², Number of potentials: 7, Number of rows: 1, Number of poles per row: 7, family of articles: MKDSFW 1.5, pitch:5 mm, type of connection: Screw connection with traction capsule, mounting: Wave soldering, Connection direction driver/printed circuit board: 90 °, color: green, Pin arrangement: Linear pin arrangement, Pin length [P]:5 mm, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

PCB terminal block, nominal current: 17.5 A, nom. voltage: 400 V, pitch: 5 mm, number of positions: 7, connection method: Screw connection with tension sleeve, mounting: Wave soldering, conductor/PCB connection direction: 90 °, color: green
Your advantages

Well-known connection principle allows worldwide useLow temperature rise, thanks to maximum contact forceAllows connection of two conductorsStand-offs enable the PCB to be cleaned or sealedThe latching on the side enables various numbers of positions to be combinedKey Commercial Data

Orderkey 1706907

Packing unit 1

GTIN 4046356889896

Custom tariff number 85369010

General

Range of articles MKDSFW 1,5

Rated surge voltage (III/3) 4 kV

Rated surge voltage (III/2) 4 kV

Rated surge voltage (II/2) 4 kV

Rated voltage (III/3) 250 V

Rated voltage (III/2) 400 V

Rated voltage (II/2) 630 V

Connection in acc. with standard EN-VDE

Nominal current IN 17.5 A

Nominal cross section 1.5 mm²

Solder pin surface Sn

Internal cylindrical gage A1

Stripping length 8 mm

Number of positions 7

Screw thread M3

Tightening torque, min 0.5 Nm

Tightening torque max 0.6 Nm

Connection data

Conductor cross section AWG min. 26

Conductor cross section AWG max. 14

2 conductors with same cross section, solid min. 0.14 mm²

2 conductors with same cross section, solid max. 1 mm²

2 conductors with same cross section, stranded min. 0.14 mm²

2 conductors with same cross section, stranded max. 0.75 mm²

2 conductors with same cross section, stranded, ferrules without plas...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MKDSFW 1,5/ 7 BD:1,2,23-27 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.