INDUSTRIAL COMPONENT DATA

PT 1,5/ 8-PVH-5,0-A RD BD-277 1701795 PHOENIX CONTACT Plug

Brand: PHOENIX CONTACT | Manufacturer Part Number: PT 1,5/ 8-PVH-5,0-A RD BD-277



Manufacturer	PHOENIX CONTACT
MPN / Reference	PT 1,5/ 8-PVH-5,0-A RD BD-277
Catalog number	1701795
Category	Cable connector
Minimum order	100 Pcs
Document ID	EO-2766497B68
Generated	2026-11-19

Product Overview

Plug
Connector for printed circuit board, nominal section: 1.5 mm², color: red, nominal current: 12 A, nominal voltage (III/2): 400 V, contact surface: Tin, contact type: Female, number of potentials: 8, number of rows: 1, number of poles: 8, number of connections: 8, family of articles: PT 1.5/.. -PVH-A, pitch: 5 mm, connection type: Screw connection with wire protection bracket, screw clamping form: H1L Philipps-Recess with longitudinal groove, conductor/printed circuit board connection direction: 0 °, plug-in system: COMBICON PST 1.3, lock: without, fixing type: without, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Key Commercial Data
Orderkey 1701795
Packing unit 1
GTIN 4046356561747
Custom tariff number 85366990
Dimensions
Length [l] 11.4 mm
Width [w] 40 mm
Height [h] 11.4 mm
Pitch 5 mm

Dimension a 35 mm
General
Range of articles PT 1,5/..-PVH-A
Number of positions 8
Connection method Screw connection with wire protector
Rated voltage (III/3) 250 V
Connection in acc. with standard EN-VDE
Nominal current IN 12 A
Nominal cross section 1.5 mm²
Connection data
Conductor cross section solid min. 0.2 mm²
Conductor cross section solid max. 2.5 mm²
Conductor cross section flexible min. 0.2 mm²
Conductor cross section flexible max. 2.5 mm²
Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm²
Conductor cross section flexible, with ferrule without plastic sleeve max. 1.5 mm²
Conductor cross section flexible, with ferrule with plastic sleeve min. 0.25 mm²
Conductor cross section flexible, with ferrule with plastic sleeve max. 1.5 mm²
Conductor cross section AWG min. 26
Conductor cross section AWG max. 14
2 conductors with same cross section, solid min. 0.2 mm²
2 conductors with same cross section, solid max. 0.75 mm²
2 conductors with same cross section, stranded min. 0.2 mm²
2 conductors with same cross section, stranded max. 0.75 mm²
2 conductors with same cross section, stranded, ferrules without plastic sleeve, min. 0.25 mm²
2 conductors with same cross section, stranded, ferrules without plastic sleeve, max. 0.34 mm²
2 conductors with same cross section,...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PT 1,5/ 8-PVH-5,0-A RD BD-277 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.