

INDUSTRIAL COMPONENT DATA

PT 2,5-MT-CLT 1087698 PHOENIX CONTACT Blade interruptible terminal block, For surge protection CLIXTRAB, Sec..

Brand: PHOENIX CONTACT | Manufacturer Part Number: PT 2,5-MT-CLT

PRODUCT IMAGE\nNOT
AVAILABLE

Manufacturer	PHOENIX CONTACT
MPN / Reference	PT 2,5-MT-CLT
Catalog number	1087698
Category	(Knife) disconnect terminal block
Minimum order	50 Pcs
Document ID	EO-1B7471DFAA
Generated	2026-09-21

Product Overview

Blade interruptible terminal block, For surge protection CLIXTRAB, Sectionable measuring terminal for surge protection, rated voltage: 400 V, rated current: 20 A, connection type: Push-in connection, Sizing cross-section: 2.5 mm², cross-section: 0.14 mm² - 4 mm², mounting: NS 35/7.5, NS 35/15, color: gray

Interruptible terminal per blade, Sectional measuring terminal for surge protection, rated voltage: 400 V, rated current: 20 A, connection type: Push-in connection, section: 0.14 mm² - 4 mm², AWG: 26 - 14, length: 98.6 mm, width: 5.2 mm, colour: grey, mounting: NS 35/7.5, NS 35/15

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Modular TBs

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PT 2,5-MT-CLT with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.