INDUSTRIAL COMPONENT DATA

PT 2,5-PE/L RD/L BU/L LED 24 GN 1336344 PHOENIX CONTACT Multi-floor terminal, number of connections: 8, numb..

Brand: PHOENIX CONTACT | Manufacturer Part Number: PT 2,5-PE/L RD/L BU/L LED 24 GN



Manufacturer	PHOENIX CONTACT
MPN / Reference	PT 2,5-PE/L RD/L BU/L LED 24 GN
Catalog number	1336344
Category	Ground terminal block
Minimum order	50 Pcs
Document ID	EO-0F74D79898
Generated	2026-11-19

Product Overview

Multi-floor terminal, number of connections: 8, number of poles: 4, connection type: Push-in connection, Ground conductor connection, Sizing cross-section: 2.5 mm2, cross-section: 0.14 mm2 - 4 mm2, connection type: Push-in connection, Step floor, Sizing cross-section: 2.5 mm2, cross-section: 0.14 mm2 - 4 mm2, mounting class: NS 35/7.5, NS 35/15, color: Grey
Multi-storey terminal, number of connections: 8, number of poles: 4, connection type: Push-in connection, Ground conductor connection, Dimensioning section: 2.5 mm², cross-section: 0.14 mm² - 4 mm², connection type: Push-in connection, Pass-through floor, Dimensioning section: 2.5 mm², cross-section: 0.14 mm² - 4 mm², installation type: NS 35/7.5, NS 35/15, colour: grey
Multi-level terminal block, number of connections: 8, number of positions: 4, connection method: Push-in connection, Protective conductor connection, Rated cross section: 2.5 mm2, cross section: 0.14 mm2 - 4 mm2, connection method: Push-in connection, Feed-through level, Rated cross section: 2.5 mm2, cross section: 0.14 mm2 - 4 mm2, mounting type: NS 35/7,5, NS 35/15, color: gray

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Modular TBs

Additional Product Information

Technical dataNotesGeneral
Note When establishing a connection on the open housing side of a feed-through modular terminal block of the same series and size, the block must be provided with a cover if the expected insulation voltage is >690 V.

The max. load current must not be exceeded by the total current of all connected conductors.
Product propertiesProduct type Ground terminal block
Number of positions 4
Number of connections 8
Number of rows 4
Insulation characteristics
Overvoltage category III
Degree of pollution 3
Electrical propertiesRated surge voltage 6 kV
Connection dataNumber of connections per level 2
Nominal cross section 2.5 mm²
Cross section AWG (converted acc. to IEC)
Protective conductor connection
Stripping length 8 mm ... 10 mm
Internal cylindrical gage A3
B3
Connection in acc. with standard IEC 60947-7-2
Conductor cross section rigid 0.14 mm² ... 4 mm²
Cross section AWG 26 ... 12 (converted acc. to IEC)
Conductor cross section flexible 0.14 mm² ... 4 mm²
Conductor cross section, flexible [AWG] 26 ... 12 (converted acc. to IEC)
Conductor cross-section flexible (ferrule without plastic sleeve) 0.14 mm² ... 2.5 mm²
Flexible conductor cross section (ferrule with plastic sleeve) 0.14 mm² ... 2.5 mm²
Nominal cross section 2.5 mm²
Feed-through level
Stripping length 8 mm ... 10 mm
Connection in acc. with standard IEC 60947-7-1
Conductor cross section rigid 0.14 mm² ... 4 mm²
Cross section AWG 26 ... 12 (converted acc. to IEC)
Conductor cross section flexible 0....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PT 2,5-PE/L RD/L BU/L LED 24 GN with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.