INDUSTRIAL COMPONENT DATA

PT 2,5-QUATTRO OG 3001373 PHOENIX CONTACT Feed-through terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: PT 2,5-QUATTRO OG



Manufacturer	PHOENIX CONTACT
MPN / Reference	PT 2,5-QUATTRO OG
Catalog number	3001373
Category	Feed-through terminal block
Minimum order	50 Pcs
Document ID	EO-097B50E6F6
Generated	2026-11-19

Product Overview

Feed-through terminal block
Feed-through terminal, nominal voltage: 800 V, nominal current: 24 A, number of connections: 4, connection type: Push-in connection, Dimensioning cross-section: 2.5 mm², cross-section: 0.14 mm² - 4 mm², installation class: NS 35/7.5, NS 35/15, colour: orange

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Modular TBs

Additional Product Information

Key Commercial Data
Orderkey 3001373
Packing unit 50 pc
Minimum order quantity 50 pc
GTIN 4046356866200
Weight per Piece (excluding packing) 10.650 g
Custom tariff number 85369010
Country of origin DE (Germany)
General
Number of levels 1
Number of connections 4
Potentials 1

Nominal cross section 2.5 mm²
Color orange
Insulating material PA
Flammability rating according to UL 94 V0
Area of application Railway industry
Machine building
Plant engineering
Process industry
Rated surge voltage 8 kV
Degree of pollution 3
Overvoltage category III
Insulating material group I
Maximum power dissipation for nominal condition 0.77 W
Maximum load current 28 A (with 4 mm² conductor cross section)
Nominal current IN 24 A (at a conductor cross section of 2.5 mm²; it must not be exceeded by the total current.)
Nominal voltage UN 800 V
Open side panel Yes
Dimensions
Width 5.2 mm
End cover width 2.2 mm
Length 72.2 mm
Height 35.3 mm
Height NS 35/7,5 36.8 mm
Height NS 35/15 44.3 mm
Connection data
Connection method Push-in connection
Connection in acc. with standard IEC 60947-7-1
Conductor cross section solid min. 0.14 mm²
Conductor cross section solid max. 4 mm²
Conductor cross section AWG min. 26
Conductor cross section AWG max. 12
Conductor cross section flexible min. 0.14 mm²
Conductor cross section flexible max. 2.5 mm²
Min. AWG conductor cross section, flexible 26
Max. AWG conductor cross section, flexible 14
Conductor cross section flexible, with ferrule without plastic sleeve min. 0.14 mm²...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PT 2,5-QUATTRO OG with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.