INDUSTRIAL COMPONENT DATA

PT 2,5-TGBD 1107096 PHOENIX CONTACT Borne of the passing lane, The current and voltage are determined by the..

Brand: PHOENIX CONTACT | Manufacturer Part Number: PT 2,5-TGBD

PRODUCT IMAGE\nNOT AVAILABLE

Manufacturer	PHOENIX CONTACT
MPN / Reference	PT 2,5-TGBD
Catalog number	1107096
Category	(Knife) disconnect terminal block
Minimum order	50 Pcs
Document ID	EO-63D0517832
Generated	2026-11-19

Product Overview

Borne of the passing lane, The current and voltage are determined by the connector used., nominal voltage: 400 V, nominal current: 16 A, connection type: Connection push-in connection, number of connections: 2, section: 0.14 mm2 - 4 mm2, AWG: 26 - 12, width: 5,2 mm, height: 35,3 mm, color: grey, type of mounting: NS 35/7,5, NS 35/15
Feed-through rail terminal, Current and voltage are determined by the connector used., nominal voltage: 400 V, nominal current: 16 A, connection type: Push-in connection, Dimensioning cross-section: 2.5 mm², cross-section: 0.14 mm² - 4 mm², mounting: NS 35/7.5, NS 35/15, color: gray

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Modular TBs

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PT 2,5-TGBD with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES
Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.