INDUSTRIAL COMPONENT DATA

PTFIX 10/12X4-NS35 GN 3273622 PHOENIX CONTACT Distribution block, nom. voltage: 800 V, nominal current: 32 A..

Brand: PHOENIX CONTACT | Manufacturer Part Number: PTFIX 10/12X4-NS35 GN



Manufacturer	PHOENIX CONTACT
MPN / Reference	PTFIX 10/12X4-NS35 GN
Catalog number	3273622
Category	Feed-through terminal block
Minimum order	8 Pcs
Document ID	EO-C70385EE5D
Generated	2026-11-19

Product Overview

Distribution block, nom. voltage: 800 V, nominal current: 32 A, connection method: Push-in connection, Push-in connection, number of connections: 13, cross section: 0.2 mm² - 6 mm², AWG: 24 - 10, width: 28.6 mm, color: green, mounting type: NS 35/7,5, NS 35/15
Distribution block, number of connections: 13, connection type: Push-in connection, Branch, Sizing cross-section: 10 mm², cross-section: 0.5 mm² - 10 mm², Push-in connection, Collective connection, cross-section: 0.2 mm² - 6 mm², mounting class: NS 35/7.5, NS 35/15, color: green

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > FIX block System

Additional Product Information

Key Commercial Data
Orderkey 3273622
Packing unit 1 pc
Minimum order quantity 8 pc
Catalog page Page 453 (C-1-2019)
GTIN 4055626667423
Weight per Piece (excluding packing) 42.500 g
Custom tariff number 85369010

Country of origin PL (Poland)
Drawings
Dimensions
Standards and Regulations
Classifications
General
Connection data
Environmental Product Compliance
Drawings
Circuit diagram
Back to topGeneral
Number of levels 1
Number of connections 13
Potentials 1
Nominal cross section 4 mm²
Nominal cross section feed-in 10 mm²
Color green
Insulating material PA
Flammability rating according to UL 94 V0
Rated surge voltage 6 kV
Degree of pollution 3
Overvoltage category III
Insulating material group I
Maximum load current 63 A
Maximum total current 63 A
Nominal current IN 32 A
Nominal voltage UN 800 V
450 V
Open side panel No
Shock protection test specification DIN EN 50274 (VDE 0660-514):2002-11
Back of the hand protection guaranteed
Finger protection guaranteed
Oscillation, broadband noise test result Test passed
Test specification, oscillation, broadband noise DIN EN 50155 (VDE 0115-200):2008-03
Test spectrum Service life test category 2, bogie-mounted
Test frequency f1= 5 Hz to f2= 250 Hz
ASD level 6.12 (m/s2)2/Hz
Acceleration 3.12 g
Test duration per axis 5 h
Test directions X-, Y- and Z-axis
Shock test result Test passed
Test specification, shock test DIN EN 50155 (VDE 0115-200):2008-03
Shock form Half-sine
Acceleration 30g
Shock duration 18 ms
Number of shocks per direction 3...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PTFIX 10/12X4-NS35 GN with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.