INDUSTRIAL COMPONENT DATA

PTFIX 10/6X4-FE 3273876 PHOENIX CONTACT Block for distribution, rated voltage: 450 V, nominal current: 32 A,..

Brand: PHOENIX CONTACT | Manufacturer Part Number: PTFIX 10/6X4-FE

PRODUCT IMAGE\nNOT AVAILABLE

Manufacturer	PHOENIX CONTACT
MPN / Reference	PTFIX 10/6X4-FE
Catalog number	3273876
Category	Feed-through terminal block
Minimum order	8 Pcs
Document ID	EO-A891EE0D3F
Generated	2026-11-18

Product Overview

Block for distribution, rated voltage: 450 V, nominal current: 32 A, type of Connection: Connection push-in Connection push-in connection, number of connections: 7, section: 0,2 mm2-6 mm2, AWG: 24-10, width: 27.9 mm, height: 21,7 mm, color: black/yellow, type of mounting: latch on adapter for rail
Distribution block, nominal voltage: 450 V, nominal current: 57 A, number of connections: 7, connection type: Push-in connection, Collective connection, Dimensioning section: 10 mm², section: 0.5 mm² - 10 mm², Push-in connection, Derivation, Dimensioning section: 4 mm², section: 0.2 mm² - 6 mm², mounting class: interlock in rail adapter, Direct mounting with a flange, Aerial color: black/yellow

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > FIX block System

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PTFIX 10/6X4-FE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.