INDUSTRIAL COMPONENT DATA

PTFIX 10/6X4-NS35-FE 3273612 PHOENIX CONTACT Block for distribution, rated voltage: 450 V, nominal current: ..

Brand: PHOENIX CONTACT | Manufacturer Part Number: PTFIX 10/6X4-NS35-FE



Manufacturer	PHOENIX CONTACT
MPN / Reference	PTFIX 10/6X4-NS35-FE
Catalog number	3273612
Category	Feed-through terminal block
Minimum order	8 Pcs
Document ID	EO-92B988CE96
Generated	2026-11-18

Product Overview

Block for distribution, rated voltage: 450 V, nominal current: 32 A, type of Connection: Connection push-in Connection push-in connection, number of connections: 7, section: 0,2 mm2-6 mm2, AWG: 24-10, width: 28.6 mm, color: black/yellow, type of mounting: NS 35/7,5, NS 35/15
Distribution block, rated voltage: 800 V, rated current: 57 A, number of connections: 7, connection type: Push-in connection, Collective connection, Sizing cross-section: 10 mm², cross-section: 0.5 mm² - 10 mm², Push-in connection, Shunt, Sizing cross-section: 4 mm², cross-section: 0.2 mm² - 6 mm², mounting class: NS 35/7.5, NS 35/15, color: black/yellow
Distributor block, rated voltage: 800 V, rated current: 41 A, number of connections: 7, connection type: Push-in connection, Socket, Dimensioning cross-section: 4 mm2, cross-section: 0.2 mm2 - 6 mm2, Push-in connection, Collective connection, Dimensioning section: 10 mm2, cross-section: 0.5 mm2 - 10 mm2, mounting type: NS 35/7.5, NS 35/15, colour: black/yellow

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > FIX block System

Additional Product Information

Technical dataNotesGeneral notes
note The maximum load current of the individual connection points must not be exceeded.
For power distribution applications, IEC 60364-4-43:2008, as amended + Corrigendum Ott. 2008 (DIN VDE 0100-430:2010-10) section 433.2 ff!
Article featuresProduct Type Distribution terminal
Number of connections 7

Number of rows 1
Potential 1
Data maintenance status
Article review 01
Insulation characteristics
Overvoltage Category Iii
Degree of pollution 3
Electrical characteristicsSizing Impulse Voltage 6 kV
Maximum power dissipation under nominal conditions 1.02 W
Connection dataFeeding Yes
Number of connections per plan 7
Nominal cross-section 4 mm²
AWG Sizing Section 10
Grip
Length of the section to be stripped 10 mm ... 12 mm
Gauge Pad A4
Standard-compliant connection IEC 60947-7-1
Rigid conductor cross-section 0.2 mm² ... 6 mm²
Conductor cross-section AWG 24 ... 10 (converted according to IEC)
Flexible conductor cross-section 0.2 mm² ... 4 mm²
Flexible conductor cross-section [AWG] 24 ... 12 (converted according to IEC)
Flexible conductor cross-section (cable lug without insulation collar) 0.2 mm² ... 4 mm²
Flexible conductor cross-section (plastic lug and collar) 0.2 mm² ... 4 mm²
2 conductors of identical cross-section flexible with TWIN ferrule with plastic collar 0.5 mm² ... 1 mm²
Rated current 41 A
Maximum load current 41 A (with 6 mm² conductor connection)
Maximum cumulative current 63 A
Nominal voltage 800 V
Nominal cross-section 4 mm²
Collecti...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PTFIX 10/6X4-NS35-FE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.