INDUSTRIAL COMPONENT DATA

PTFIX 12X2,5-NS35A OG 3273172 PHOENIX CONTACT Distribution block

Brand: PHOENIX CONTACT | Manufacturer Part Number: PTFIX 12X2,5-NS35A OG



Manufacturer	PHOENIX CONTACT
MPN / Reference	PTFIX 12X2,5-NS35A OG
Catalog number	3273172
Category	Feed-through terminal block
Minimum order	8 Pcs
Document ID	EO-9F8D11CC9A
Generated	2026-11-18

Product Overview

Distribution block
Distribution block, Block with horizontal alignment, nominal voltage: 690 V, nominal current: 24 A, number of connections: 12, connection type: Push-in connection, cross-section: 0.14 mm² - 4 mm², mounting class: NS 35/7.5, NS 35/15, color: orange
Distribution block, Block with horizontal orientation, Nominal voltage: 690 V, Rated current: 24 A, Number of connections: 12, Connection type: Push-in connection, Cross-section: 0.14 mm2 - 4 mm2, Mounting type: NS 35/7.5, NS 35/15, Colour: orange

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > FIX block System

Additional Product Information

Key Commercial Data
Orderkey 3273172
Packing unit 8 pc
Minimum order quantity 8 pc
Catalog page Page 141 (C-1-2017)
GTIN 4055626391472
Weight per Piece (excluding packing) 26.400 g
Custom tariff number 85369010
Country of origin PL (Poland)

General
Note Notes on operation The blocks can be bridged with one another via the conductor shaft. For corresponding plug-in bridges, see accessories
Number of levels 1
Number of connections 12
Potentials 1
Nominal cross section 2.5 mm²
Color orange
Insulating material PA
Flammability rating according to UL 94 V0
Rated surge voltage 6 kV
Degree of pollution 3
Overvoltage category III
Insulating material group I
Maximum power dissipation for nominal condition 0.77 W (the value is based on one connection block and is multiplied according to the pin assignment)
Maximum load current 32 A
Maximum total current 48 A
Nominal current IN 24 A
Nominal voltage UN 690 V
Open side panel No
Shock protection test specification DIN EN 50274 (VDE 0660-514):2002-11
Back of the hand protection guaranteed
Finger protection guaranteed
Result of surge voltage test Test passed
Surge voltage test setpoint 9.8 kV
Result of power-frequency withstand voltage test Test passed
Power frequency withstand voltage setpoint 1.89 kV
Result of the test for mechanical stability of terminal points (5 x conductor connection) Test passed
Result of bending test Test passed
Bending test rotation speed 10 rpm
Bending test turns 135
Bending test conductor cross section/weight 0.14...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PTFIX 12X2,5-NS35A OG with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.