INDUSTRIAL COMPONENT DATA

GMSTB 2,5/ 2-ST-7,62 BD:N,L 1701556 PHOENIX CONTACT Plug

Brand: PHOENIX CONTACT | Manufacturer Part Number: GMSTB 2,5/ 2-ST-7,62 BD:N,L



Manufacturer	PHOENIX CONTACT
MPN / Reference	GMSTB 2,5/ 2-ST-7,62 BD:N,L
Catalog number	1701556
Category	Cable connector
Minimum order	50 Pcs
Document ID	EO-4EB93352E1
Generated	2026-11-19

Product Overview

Plug
Connector for printed circuit board, nominal section: 2.5 mm², color: green, rated current: 12 A, sizing voltage (III/2): 630 V, surface contacts: Tin, contact type: Connection female, Number of potentials: 2, Number of rows: 1, Number of poles per row: 2, number of connections: 2, article family: GMSTB 2.5/.. -ST, pitch: 7.62 mm, connection type: Screw connection with traction capsule, connection direction conductor/printed circuit board: 0 °,Stecksystem: CLASSIC COMBICON, Lock: without, type of packaging: boxed packaging

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Key Commercial Data
Orderkey 1701556
Packing unit 1
GTIN 4046356543729
Custom tariff number 85366990
Dimensions
Length [l] 18.2 mm
Width [w] 13.24 mm
Height [h] 15 mm
Pitch 7.62 mm

Dimension a 7.62 mm
General
Range of articles GMSTB 2,5/..-ST
Number of positions 2
Connection method Screw connection with tension sleeve
Insulating material group I
Rated surge voltage (III/3) 6 kV
Rated surge voltage (III/2) 6 kV
Rated surge voltage (II/2) 6 kV
Rated voltage (III/3) 400 V
Rated voltage (III/2) 630 V
Rated voltage (II/2) 1000 V
Connection in acc. with standard EN-VDE
Nominal current IN 12 A
Nominal cross section 2.5 mm²
Insulating material PA
Flammability rating according to UL 94 V0
Internal cylindrical gage A3
Stripping length 7 mm
Screw thread M3
Tightening torque, min 0.5 Nm
Tightening torque max 0.6 Nm
Connection data
Conductor cross section solid min. 0.2 mm²
Conductor cross section solid max. 2.5 mm²
Conductor cross section flexible min. 0.2 mm²
Conductor cross section flexible max. 2.5 mm²
Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm²
Conductor cross section flexible, with ferrule without plastic sleeve max. 2.5 mm²
Conductor cross section flexible, with ferrule with plastic sleeve min. 0.25 mm²
Conductor cross section flexible, with ferrule with plastic sleeve max. 2.5 mm²
Conductor cross section AWG min. 24
Conductor cross section AWG max. 12
2 conductors with same cross section, solid min. 0.2 mm²
2 conductors with same cros...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / GMSTB 2,5/ 2-ST-7,62 BD:N,L with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.