
INDUSTRIAL COMPONENT DATA

PTFIX 4/18X1,5-NS35 GY 1047454 PHOENIX CONTACT Distribution block, nom. voltage: 500 V, nominal current: 17...

Brand: PHOENIX CONTACT | Manufacturer Part Number: PTFIX 4/18X1,5-NS35 GY



Manufacturer	PHOENIX CONTACT
MPN / Reference	PTFIX 4/18X1,5-NS35 GY
Catalog number	1047454
Category	Feed-through terminal block
Minimum order	20 Pcs
Document ID	EO-DBFBF8B6EB
Generated	2026-11-19

Product Overview

Distribution block, nom. voltage: 500 V, nominal current: 17.5 A, connection method: Push-in connection, Push-in connection, number of connections: 19, cross section: 0.14 mm² - 2.5 mm², AWG: 26 - 14, width: 21.6 mm, color: gray, mounting type: NS 35/7,5, NS 35/15
Distribution block, Vertically aligned block with integrated power supply, nominal voltage: 500 V, nominal current: 17.5 A, number of connections: 19, connection type: Push-in connection, Branch, cross-section: 0.14 mm² - 2.5 mm², Collective connection, Dimensioning cross-section: 4 mm², cross-section: 0.2 mm² - 6 mm², mounting class: NS 35/7.5, NS 35/15, colour: grey

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > FIX block System

Additional Product Information

Key Commercial Data
Orderkey 1047454
Packing unit 1 pc
Minimum order quantity 20 pc
Catalog page Page 437 (C-1-2019)
GTIN 4055626665597
Weight per Piece (excluding packing) 23.000 g
Custom tariff number 85369010
Country of origin PL (Poland)

Drawings
Dimensions
Standards and Regulations
General
Connection data
Classifications
Drawings
Circuit diagram
Back to topGeneral
Number of levels 1
Number of connections 19
Nominal cross section 1.5 mm²
Nominal cross section feed-in 4 mm²
Color gray
Insulating material PA
Flammability rating according to UL 94 V0
Rated surge voltage 6 kV
Degree of pollution 3
Overvoltage category III
Insulating material group I
Maximum load current 22 A (with a 2.5 mm² conductor cross section)
Maximum total current 32 A
Nominal current IN 17.5 A
Nominal voltage UN 500 V
Maximum load current 41 A (with 6 mm² conductor cross section)
Maximum total current 41 A
Nominal current IN 41 A
Open side panel No
Back to topDimensions
Width 21.6 mm
Length 58.1 mm
Height NS 35/7,5 28.4 mm
Height NS 15 26.4 mm
Back to topConnection data
Connection method Push-in connection
Stripping length 8 mm ... 10 mm
Connection in acc. with standard IEC 60947-7-1
Conductor cross section solid min. 0.14 mm²
Conductor cross section solid max. 2.5 mm²
Conductor cross section AWG min. 26
Conductor cross section AWG max. 14
Conductor cross section flexible min. 0.14 mm²
Conductor cross section flexible max. 1.5 mm²
Min. AWG conductor cross section, flexible 26
Max. AWG conductor cross....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PTFIX 4/18X1,5-NS35 GY with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.