INDUSTRIAL COMPONENT DATA

PTFIX 4/6X1,5-FE 1047477 PHOENIX CONTACT Block for distribution, bridged internally, rated voltage: 450 V, r..

Brand: PHOENIX CONTACT | Manufacturer Part Number: PTFIX 4/6X1,5-FE

PRODUCT IMAGE\nNOT AVAILABLE

Manufacturer	PHOENIX CONTACT
MPN / Reference	PTFIX 4/6X1,5-FE
Catalog number	1047477
Category	Feed-through terminal block
Minimum order	20 Pcs
Document ID	EO-F63CD92BDA
Generated	2026-11-18

Product Overview

Block for distribution, bridged internally, rated voltage: 450 V, rated current: 17,5 A, type of Connection: Connection push-in Connection push-in connection, number of connections: 7, section: 0.14 mm2-2.5 mm2, AWG: 26-14, width: 19 mm, height: 17.7 mm, color: black/yellow, type of mounting: latch on adapter for rail
Distribution block, internally bridged, rated voltage: 450 V, rated current: 17.5 A, number of connections: 7, connection type: Push-in connection, Shunt, cross-section: 0.14 mm² - 2.5 mm², Collective connection, Sizing cross-section: 4 mm², cross-section: 0.2 mm² - 6 mm², mounting class: interlock in rail adapter, Direct mounting with a flange, Aerial, color: black/yellow

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > FIX block System

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PTFIX 4/6X1,5-FE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.