
INDUSTRIAL COMPONENT DATA

PTFIX 4X1,5-FE 1046620 PHOENIX CONTACT Distribution block, bridged internally, The blocks can be bridged wit..

Brand: PHOENIX CONTACT | Manufacturer Part Number: PTFIX 4X1,5-FE



Manufacturer	PHOENIX CONTACT
MPN / Reference	PTFIX 4X1,5-FE
Catalog number	1046620
Category	Feed-through terminal block
Minimum order	30 Pcs
Document ID	EO-FCA3B45547
Generated	2026-11-19

Product Overview

Distribution block, bridged internally, The blocks can be bridged with one another via the conductor shaft. For corresponding plug-in bridges, see accessories, nom. voltage: 450 V, nominal current: 17.5 A, connection method: Push-in connection, number of connections: 4, cross section: 0.14 mm² - 2.5 mm², AWG: 26 - 14, width: 8.3 mm, height: 17.7 mm, color: black/yellow, mounting type: for snapping onto a DIN rail adapter
Distribution block, internally bridged, rated voltage: 450 V, rated current: 17.5 A, number of connections: 4, connection type: Push-in connection, cross-section: 0.14 mm² - 2.5 mm², mounting type: interlock in rail adapter, Direct mounting with a flange, Aerial, color: black/yellow
Distribution block, bridged internally, nom. voltage: 450 V, nominal current: 17.5 A, number of connections: 4, connection method: Push-in connection, cross section: 0.14 mm2 - 2.5 mm2, mounting type: for snapping onto a DIN rail adapter, Direct mounting with flange, Free-hanging, color: black/yellow

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > FIX block System

Additional Product Information

Technical dataNotesNotes on operation the blocks can be bridged with one another via the conductor shaft, for corresponding plug-in bridges, see accessories
General
Note The maximum load current of a single clamping unit must not be exceeded.
Product propertiesProduct type Distributor terminal block
Number of connections 4

Number of rows 1
Potentials 1
Data management status
Article revision 03
Insulation characteristics
Overvoltage category III
Degree of pollution 3
Electrical propertiesRated surge voltage 6 kV
Maximum power dissipation for nominal condition 0.56 W
Connection dataNumber of connections per level 4
Nominal cross section 1.5 mm²
Rated cross section AWG 14
Stripping length 8 mm ... 10 mm
Internal cylindrical gage A2 / B1
Connection in acc. with standard IEC 60998-2-2
Conductor cross section rigid 0.14 mm² ... 2.5 mm²
Cross section AWG 26 ... 14 (converted acc. to IEC)
Conductor cross section flexible 0.14 mm² ... 1.5 mm²
Conductor cross section, flexible [AWG] 26 ... 16 (converted acc. to IEC)
Conductor cross-section flexible (ferrule without plastic sleeve) 0.14 mm² ... 1.5 mm²
Flexible conductor cross section (ferrule with plastic sleeve) 0.14 mm² ... 1.5 mm²
Nominal current 17.5 A
Maximum load current 22 A
Maximum total current 26 A
Nominal voltage 450 V
Connection cross sections directly pluggable
Conductor cross section rigid 0.34 mm² ... 2.5 mm²
Conductor cross section, rigid [AWG] 26 ... 14 (converted acc. to IEC)
Conductor cross-section flexible (ferrul...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PTFIX 4X1,5-FE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.