INDUSTRIAL COMPONENT DATA

SPC 5/ 2-ST-7,62 BK 1707524 PHOENIX CONTACT Plug-in part, rated current: 41 A, number of poles: 2, pitch: 7...

Brand: PHOENIX CONTACT | Manufacturer Part Number: SPC 5/ 2-ST-7,62 BK

PRODUCT IMAGE\nNOT AVAILABLE

Manufacturer	PHOENIX CONTACT
MPN / Reference	SPC 5/ 2-ST-7,62 BK
Catalog number	1707524
Category	Cable connector
Minimum order	50 Pcs
Document ID	EO-AF2D005266
Generated	2026-11-19

Product Overview

Plug-in part, rated current: 41 A, number of poles: 2, pitch: 7.62 mm, connection type: Push-in spring connection, color: black, contact surface: Tin
Connector for printed circuit board, nominal section: 6 mm², color: black, nominal current: 41 A, nominal voltage (III/2): 1000 V, contact surface: Tin, contact type: Female, number of potentials: 2, number of rows: 1, number of poles: 2, number of connections: 2, family of articles: SPC 5/.. -ST, pitch: 7.62 mm, connection type: Push-in spring connection, driver/printed circuit board connection direction: 0°, clamping hook: - Clamping hook, plug-in system: COMBICON PC 5, locking: without, fixing type: without, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Plug component, nominal current: 41 A, number of positions: 2, pitch: 7.62 mm, connection method: Push-in spring connection, color: black, contact surface: Tin
Your advantages
Time saving push-in connection, tools not requiredDefined contact force ensures that contact remains stable over the long termClamping space opened by means of fixed screwdriver enables convenient conductor connectionIntegrated double steel spring provides additional safety in the event of temperature and power fluctuationsOptimized for tight installation situations: operation and conductor connection from one direction600 V UL approval in the smallest of dimensionsKey Commercial Data
Orderkey 1707524

Packing unit 1
GTIN 4046356927284
Custom tariff number 85366990
General
Range of articles SPC 5/..-ST
Type of contact Female connector
Number of positions 2
Connection method Push-in spring connection
Rated voltage (III/3) 1000 V
Connection in acc. with standard EN-VDE
Nominal current IN 41 A
Nominal cross section 6 mm²
Connection data
Conductor cross section solid min. 0.2 mm²
Conductor cross section solid max. 10 mm²
Conductor cross section flexible min. 0.2 mm²
Conductor cross section flexible max. 6 mm²
Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm²
Conductor cross section flexible, with ferrule without plastic sleeve max. 6 mm²
Conductor cross section flexible, with ferrule with plastic sleeve min. 0.25 mm²
Conductor cross section flexible, with ferrule with plast...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SPC 5/ 2-ST-7,62 BK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.