INDUSTRIAL COMPONENT DATA

PTFIX 6/6X2,5-MT BU 1487214 PHOENIX CONTACT Function distributor block, Base terminal with power supply and ..

Brand: PHOENIX CONTACT | Manufacturer Part Number: PTFIX 6/6X2,5-MT BU



Manufacturer	PHOENIX CONTACT
MPN / Reference	PTFIX 6/6X2,5-MT BU
Catalog number	1487214
Category	Feed-through terminal block
Minimum order	8 Pcs
Document ID	EO-42A02AEBEC
Generated	2026-11-18

Product Overview

Function distributor block, Base terminal with power supply and disconnector blade in the branches, separation with screwdriver, nominal voltage: 400 V, nominal current: 20 A, Derivation, connection type: Push-in connection, Dimensioning section: 2.5 mm2, section: 0.14 mm2 - 4 mm2, Collective connection, connection type: Push-in connection, Dimensioning section: 6 mm2, section: 0.5 mm2 - 10 mm2, Mounting: Interlock on Rail Adapter, Direct Mount with One Flange, Aerial, Color: Blue
Block for distribution
Distribution block, Basic terminal block with feed-in and disconnect knife in the branches, disconnection via screwdriver, nom. voltage: 400 V, nominal current: 20 A, Load contact, connection method: Push-in connection, Rated cross section: 2.5 mm2, cross section: 0.14 mm2 - 4 mm2, Line contact, connection method: Push-in connection, Rated cross section: 6 mm2, cross section: 0.5 mm2 - 10 mm2, mounting: for snapping onto a DIN rail adapter, Direct mounting with flange, Free-hanging, color: blue

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > FIX block System

Additional Product Information

Technical dataProduct propertiesProduct type Distributor terminal block
Number of connections 7
Number of rows 1
Insulation characteristics
Overvoltage category III

Degree of pollution 3
Electrical propertiesRated surge voltage 6 kV
Maximum power dissipation for nominal condition 0.77 W
Connection dataService Entrance yes
Number of connections per level 7
Nominal cross section 2.5 mm²
Load contact
Stripping length 8 mm ... 10 mm
Internal cylindrical gage A3
B3
Connection in acc. with standard IEC 60947-7-1
Conductor cross section rigid 0.14 mm² ... 4 mm²
Cross section AWG 26 ... 12 (converted acc. to IEC)
Conductor cross section flexible 0.14 mm² ... 2.5 mm²
Conductor cross section, flexible [AWG] 26 ... 14 (converted acc. to IEC)
Conductor cross-section flexible (ferrule without plastic sleeve) 0.14 mm² ... 2.5 mm²
Flexible conductor cross section (ferrule with plastic sleeve) 0.14 mm² ... 2.5 mm²
Nominal current 20 A
Maximum load current 20 A (with 4 mm² conductor cross section)
Maximum total current 57 A (with 10 mm² conductor cross section)
Nominal voltage 400 V
Note The IEC 60947-7-1 standard applies for the use of mounting accessories.
Nominal cross section 2.5 mm²
Line contact
Stripping length 10 mm ... 12 mm
Internal cylindrical gage A5
B4
Conductor cross section rigid 0.5 mm² ... 10 mm²
Cross section AWG 20 ... 8 (converted acc. to IEC)
Conductor cross section flexible 0.5 mm² ... 10 mm²
Conductor cross section, flexible [AWG] 20 ... 8 (converted acc. to IEC)
Conduc...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PTFIX 6/6X2,5-MT BU with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.