INDUSTRIAL COMPONENT DATA

PTI 2,5-PE/LO/LO 3213937 PHOENIX CONTACT Installation ground terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: PTI 2,5-PE/LO/LO



Manufacturer	PHOENIX CONTACT
MPN / Reference	PTI 2,5-PE/LO/LO
Catalog number	3213937
Category	Multi level installation terminal block
Minimum order	50 Pcs
Document ID	EO-B80641DACC
Generated	2026-11-19

Product Overview

Installation ground terminal block
Ground terminal for distribution, without drive compressor, nominal voltage: 400 V, nominal current: 24 A, Push-in connection, 1., 2. and 3rd floor, Dimensioning section: 4 mm², cross-section: 0.14 mm² - 4 mm², Push-in connection, mounting class: NS 35/7.5, NS 35/15, color: gray

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Modular TBs

Additional Product Information

Key Commercial Data
Orderkey 3213937
Packing unit 50 pc
Minimum order quantity 50 pc
GTIN 4046356979719
Weight per Piece (excluding packing) 18.020 g
Custom tariff number 85369010
Country of origin DE (Germany)
General
Note Assembly instructions:For secure fastening of the neutral busbar, supports must be set at the beginning and end of each terminal strip as well as every 20 cm on longer terminal strips.
Number of levels 3

Number of connections 5
Potentials 2
Nominal cross section 4 mm²
Color gray
Insulating material PA
Flammability rating according to UL 94 V0
Rated surge voltage 4 kV
6 kV
Degree of pollution 3
Overvoltage category III
Insulating material group I
Maximum power dissipation for nominal condition 1.02 W (the value is multiplied when connecting multiple levels)
Maximum load current 30 A (with 4 mm² conductor cross section and 3-pos. terminal block)
Nominal current IN 24 A (with 4 mm² conductor cross section)
Nominal voltage UN 400 V (phase conductor/phase conductor)
250 V (phase conductor/PE)
Open side panel Yes
Relative insulation material temperature index (Elec., UL 746 B) 130 °C
Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21)) 125 °C
Static insulating material application in cold -60 °C
Behavior in fire for rail vehicles (DIN 5510-2) Test passed
Flame test method (DIN EN 60695-11-10) V0
Oxygen index (DIN EN ISO 4589-2) >32 %
NF F16-101, NF F10-102 Class I 2
NF F16-101, NF F10-102 Class F 2
Surface flammability NFPA 130 (ASTM E 162) p...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PTI 2,5-PE/LO/LO with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.