INDUSTRIAL COMPONENT DATA

PTME 4 WH 3212140 PHOENIX CONTACT Test disconnect terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: PTME 4 WH



Manufacturer	PHOENIX CONTACT
MPN / Reference	PTME 4 WH
Catalog number	3212140
Category	(Knife) disconnect terminal block
Minimum order	50 Pcs
Document ID	EO-85AF2BAF31
Generated	2026-11-19

Product Overview

Test disconnect terminal block
Borne interrupts. for circ. measurement, nominal voltage: 500 V, nominal current: 24 A, number of connections: 2, connection type: Push-in connection, 1st floor, Sizing cross-section: 4 mm², cross-section: 0.2 mm² - 6 mm², mounting class: NS 35/7.5, NS 35/15, color: white
Test Shut-Off Terminal Block, Nominal Voltage: 500 V, Rated Current: 24 A, Number of Connections: 2, Connection Type: Push-in Connection, 1st Stage, Reference Section: 4 mm2, Cross-Section: 0.2 mm2 - 6 mm2, Installation Type: NS 35/7.5, NS 35/15, Colour: White

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Modular TBs

Additional Product Information

Key Commercial Data
Orderkey 3212140
Packing unit 50 pc
GTIN 4046356681834
Weight per Piece (excluding packing) 14.130 g
Custom tariff number 85369010
Country of origin PL (Poland)
General
Number of levels 1

Number of connections 2
Potentials 1
Nominal cross section 4 mm²
Color white
Insulating material PA
Flammability rating according to UL 94 V0
Rated surge voltage 6 kV
Overvoltage category III
Insulating material group I
Maximum power dissipation for nominal condition 1.02 W
Maximum load current 24 A
Nominal current IN 24 A
Nominal voltage UN 500 V
Open side panel Yes
Dimensions
Width 6.2 mm
End cover width 2.2 mm
Length 70.5 mm
Height 48.8 mm
Height NS 35/7,5 49.5 mm
Height NS 35/15 57 mm
Connection data
Connection method Push-in connection
Connection in acc. with standard IEC 60947-7-1
Conductor cross section solid min. 0.2 mm²
Conductor cross section solid max. 6 mm²
Conductor cross section AWG min. 24
Conductor cross section AWG max. 10
Conductor cross section flexible min. 0.2 mm²
Conductor cross section flexible max. 4 mm²
Min. AWG conductor cross section, flexible 24
Max. AWG conductor cross section, flexible 12
Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm²
Conductor cross section flexible, with ferrule without plastic sleeve max. 4 mm²
Conductor cross section flexible, with ferrule with plastic sleeve min. 0.25 mm²
Conductor cross section flexible, with ferrule with plastic sleeve max. 4 mm²
2 conductors with same cross sectio...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PTME 4 WH with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.