INDUSTRIAL COMPONENT DATA

# PTPOWER 50 P-FE-F 1091233 PHOENIX CONTACT High-current terminal block, with test socket, nom. voltage: 1000 ..

**Brand: PHOENIX CONTACT | Manufacturer Part Number: PTPOWER 50 P-FE-F**



| | |
|---|---|
| Manufacturer | PHOENIX CONTACT |
| MPN / Reference | PTPOWER 50 P-FE-F |
| Catalog number | 1091233 |
| Category | Feed-through terminal block |
| Minimum order | 10 Pcs |
| Document ID | EO-1587261754 |
| Generated | 2026-11-19 |

## Product Overview

High-current terminal block, with test socket, nom. voltage: 1000 V AC / 1500 V DC, nominal current: 150 A, connection method: Power-Turn connection, number of connections: 2, number of positions: 1, cross section: 10 mm² - 70 mm², AWG: 8 - 2/0, width: 20 mm, color: black/yellow, mounting type: direct screw connection
Power terminal block, with test socket, nominal voltage: 1000 V, nominal current: 150 A, number of connections: 2, number of poles: 1, connection type: PowerTurn connection, 1st floor, cross-section: 10 mm² - 70 mm², mounting type: direct screwed, color: black/yellow

STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

| | |
|---|---|
| Catalog path | PHOENIX CONTACT > Modular TBs |

## Additional Product Information

Key Commercial Data
Orderkey 1091233
Packing unit 1
GTIN 4055626903231
Custom tariff number 85369010
Drawings
Dimensions
Standards and Regulations

General
Connection data
Classifications
Drawings
Circuit diagram
Back to topGeneral
Number of positions 1
Number of levels 1
Number of connections 2
Potentials 1
Nominal cross section 50 mm²
Color black/yellow
Insulating material PA
Flammability rating according to UL 94 V0
Rated surge voltage 8 kV
Degree of pollution 3
Overvoltage category III
Insulating material group I
Maximum load current 150 A (with 50 mm² conductor cross section)
Nominal current IN 150 A
Nominal voltage UN 1000 V AC
1500 V DC
Open side panel No
Back to topDimensions
Width 20 mm
Length 101 mm
Hole diameter 6.5 mm
Drill hole spacing 123.4 mm
Pitch 20 mm
Back to topConnection data
Connection 1 level
Connection method Power-Turn connection
Stripping length 30 mm ... 32 mm
Connection in acc. with standard IEC 60947-7-1
Conductor cross section solid min. 10 mm²
Conductor cross section solid max. 70 mm²
Conductor cross section AWG min. 8
Conductor cross section AWG max. 2/0
Conductor cross section flexible min. 10 mm²
Conductor cross section flexible max. 70 mm²
Min. AWG conductor cross section, flexible 8
Max. AWG conductor cross section, flexible 2/0
Conductor cross section flexible, with ferrule without plastic sleeve min. 10 mm²
Conductor cross section flexible, with ferrule without plastic sleeve max. 50 mm²
Conductor cross section flexible, with ferrule with....

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PTPOWER 50 P-FE-F with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.