INDUSTRIAL COMPONENT DATA

PTS 1,5/10-PH-5,0 BK 1705166 PHOENIX CONTACT Plug-in part, rated current: 10 A, number of poles: 10, pitch: ..

Brand: PHOENIX CONTACT | Manufacturer Part Number: PTS 1,5/10-PH-5,0 BK

PRODUCT IMAGE\nNOT AVAILABLE

Manufacturer	PHOENIX CONTACT
MPN / Reference	PTS 1,5/10-PH-5,0 BK
Catalog number	1705166
Category	Cable connector
Minimum order	500 Pcs
Document ID	EO-38E35B10BD
Generated	2026-11-19

Product Overview

Plug-in part, rated current: 10 A, number of poles: 10, pitch: 5 mm, connection type: Push-in spring connection, color: black, contact surface: Tin
Connector for printed circuit board, nominal section: 1.5 mm², color: black, nominal current: 10 A, nominal voltage (III/2): 400 V, contact surface: Tin, contact type: Female, number of potentials: 10, number of rows: 1, number of poles: 10, number of connections: 10, family of articles: PTS 1.5/.. -PH, pitch: 5mm, connection type: Push-in spring connection, driver/printed circuit board connection direction: 0°, plug-in system: COMBICON PST 1.3, lock: without, fixing type: without, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Plug component, nominal current: 10 A, number of positions: 10, pitch: 5 mm, connection method: Push-in spring connection, color: black, contact surface: Tin
Your advantages
Time saving push-in connection, tools not requiredDefined contact force ensures that contact remains stable over the long termIntuitive use through colour coded actuation leverQuick and convenient testing using integrated test optionLargest possible clamping space in a small component sizeKey Commercial Data
Orderkey 1705166
Packing unit 1
GTIN 4046356756105

Custom tariff number 85366990
General
Range of articles PTS 1,5/..-PH
Type of contact Female connector
Number of positions 10
Connection method Push-in spring connection
Rated voltage (III/3) 250 V
Nominal current IN 10 A
Nominal cross section 1.5 mm²
Connection data
Conductor cross section solid min. 0.2 mm²
Conductor cross section solid max. 2.5 mm²
Conductor cross section flexible min. 0.2 mm²
Conductor cross section flexible max. 2.5 mm²
Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm²
Conductor cross section flexible, with ferrule without plastic sleeve max. 1.5 mm²
Conductor cross section flexible, with ferrule with plastic sleeve min. 0.25 mm²
Conductor cross section flexible, with ferrule with plastic sleeve max. 1.5 mm²
Conductor cross section AWG min. 26
Conductor cross section AWG max. 14
Environmental Product Compliance
China RoHS Environmentally friendly use period: unlimited = EFUP-e
No hazardous subst...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PTS 1,5/10-PH-5,0 BK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.