

INDUSTRIAL COMPONENT DATA

PTS 1,5/ 3-5,0-H AP TRB BK 1709567 PHOENIX CONTACT PCB terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: PTS 1,5/ 3-5,0-H AP TRB BK



Manufacturer	PHOENIX CONTACT
MPN / Reference	PTS 1,5/ 3-5,0-H AP TRB BK
Catalog number	1709567
Category	Printed circuit board terminal
Minimum order	250 Pcs
Document ID	EO-C91F4CC34D
Generated	2026-09-30

Product Overview

PCB terminal block

Terminal block for printed circuit board, number of potentials: 3, number of rows: 1, number of poles per row: 3, family of articles: PTSH 1.5/..-H, pitch: 5 mm, connection type: Push-in connection, mounting: Wave soldering, conductor/printed circuit board connection direction: 0 °, color: black, Pin arrangement: Linear pin arrangement, Pin length [P]: 2.5 mm, number of solder pins per potential: 1, packaging type: boxed

Printed circuit board terminal, number of potentials: 3, number of rows: 1, number of positions per row: 3, product range: PTSH 1,5/..-H, pitch: 5 mm, connection method: Push-in connection, mounting: Wave soldering, conductor/PCB connection direction: 0 °, color: black, Pin layout: Linear pinning, Solder pin [P]: 2.5 mm, number of solder pins per potential: 1, type of packaging: packed in cardboard

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

Additional Product Information

Technical dataProduct propertiesProduct type Printed circuit board terminal

Product family PTSH 1,5/..-H

Product line COMBICON Terminals S

Type PC termination block

Number of positions 3

Pitch 5 mm

Number of connections 3

Number of rows 1
Number of potentials 3
Pin layout Linear pinning
Solder pins per potential 1
Data management status
Article revision 04
MountingMounting type Wave soldering
Pin layout Linear pinning
Material specificationsMaterial data - housing
Color (Housing) black (9005)
DimensionsDimensional drawing
Pitch 5 mm
Width [w] 15 mm
Height [h] 16.8 mm
Length [l] 10.5 mm
Installed height 14.3 mm
Solder pin length [P] 2.5 mm
PCB design
Hole diameter 1.2 mm
Environmental and real-life conditionsAmbient conditions
Ambient temperature (operation) -40 °C (dependent on the derating curve)
Ambient temperature (storage/transport) -40 °C ... 70 °C
Ambient temperature (assembly) -5 °C ... 100 °C
Packaging specificationsType of packaging packed in cardboard

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PTS 1,5/ 3-5,0-H AP TRB BK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.