

INDUSTRIAL COMPONENT DATA

PTSA 1,5/ 2-3,5-Z 4RZ MIXC 1798090 PHOENIX CONTACT

Terminal for printed circuit board, nominal current: 8 A,..

Brand: PHOENIX CONTACT | Manufacturer Part Number: PTSA 1,5/ 2-3,5-Z 4RZ MIXC



Manufacturer	PHOENIX CONTACT
MPN / Reference	PTSA 1,5/ 2-3,5-Z 4RZ MIXC
Catalog number	1798090
Category	Printed circuit board terminal
Minimum order	160 Pcs
Document ID	EO-7D4BB5A5D8
Generated	2026-09-25

Product Overview

Terminal for printed circuit board, nominal current: 8 A, rated voltage: 400 V, pitch: 3.5 mm, number of poles: 2, connection type: spring clamp push-in, mounting: Soldering by wave direction for connection conductor/pcb: 45 °, color: multicolor

Printed circuit board terminal, rated current: 8 A, sizing voltage (III/2): 400 V, nominal section: 1.5 mm², Number of potentials: 2, Number of rows: 1, Number of poles per row: 2, item family: PTSA 1.5, pitch: 3.5 mm, connection type: Push-in spring connection, mounting: Wave welding, conductor/printed circuit board connection direction: 45°, color: multicolor, Pin layout: Zigzag pins M, Pin length [P]: 3.6 mm, Packing type: boxed

PCB terminal block, nominal current: 8 A, rated voltage (III/2): 400 V, nominal cross section: 1.5 mm², number of potentials: 2, number of rows: 1, number of positions per row: 2, product range: PTSA 1,5, pitch: 3.5 mm, connection method: Push-in spring connection, mounting: Wave soldering, conductor/PCB connection direction: 45 °, color: multicolored, Pin layout: Zigzag pinning W, Solder pin [P]: 3.5 mm, number of solder pins per potential: 1, type of packaging: packed in cardboard

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Technical dataProduct propertiesType PC termination block

Product line COMBICON Terminals S

Product type Printed circuit board terminal

Product family PTSA 1,5

Number of positions 2

Pitch 3.5 mm

Number of connections 2
Number of rows 1
Number of potentials 2
Pin layout Zigzag pinning W
Solder pins per potential 1
Electrical propertiesNominal current IN 8 A
Nominal voltage UN 400 V
Degree of pollution 3
Rated voltage (III/3) 250 V
Rated surge voltage (III/3) 4 kV
Rated voltage (III/2) 400 V
Rated surge voltage (III/2) 4 kV
Rated voltage (II/2) 630 V
Rated surge voltage (II/2) 4 kV
Connection dataConnection technology
Type PC termination block
Nominal cross section 1.5 mm²
Conductor connection
Connection method Push-in spring connection
Conductor cross section rigid 0.2 mm² ... 1.5 mm²
Conductor cross section flexible 0.2 mm² ... 1.5 mm²
Conductor cross section AWG 24 ... 16
Conductor cross section flexible, with ferrule without plastic sleeve 0.25 mm² ... 1 mm²
Conductor cross section, flexible, with ferrule, with plastic sleeve 0.25 mm² ... 0.5 mm²
Stripping length 9 mm
MountingMounting type Wave soldering
Pin layout Zigzag pinning W
Connection method Push-in spring connection
Material specificationsMaterial data - contact
Note WEEE/RoHS-compliant, free of whiskers according to IEC 60068-2-82/JEDEC JESD 201
Contact material Cu alloy
Surface characteristics hot-dip tin-plated
Metal surface terminal point (top layer) Tin (4 - 8 µm Sn)
Metal surface soldering area (top layer) T...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PTSA 1,5/ 2-3,5-Z 4RZ MIXC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.