

INDUSTRIAL COMPONENT DATA

PTSA 1,5/ 2-3,5-ZI BK/GN 1806998 PHOENIX CONTACT PCB terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: PTSA 1,5/ 2-3,5-ZI BK/GN



Manufacturer	PHOENIX CONTACT
MPN / Reference	PTSA 1,5/ 2-3,5-ZI BK/GN
Catalog number	1806998
Category	Printed circuit board terminal
Minimum order	420 Pcs
Document ID	EO-712B23568A
Generated	2026-09-29

Product Overview

PCB terminal block

Terminal block for printed circuit board, nominal current: 8 A, nominal voltage (III/2): 400 V, nominal cross-section: 1.5 mm², number of potentials: 2, number of rows: 1, number of poles per row: 2, article family: PTSA 1.5, pitch: 3.5 mm, connection type: Push-in spring connection, mounting: Wave soldering, conductor connection direction/printed circuit board: 45 °, color: multicolor, Pin arrangement: Zigzag Pins W, Pin length [P]: 3.5 mm, number of welding pins per potential: 1, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

Additional Product Information

Key Commercial Data

Orderkey 1806998

Packing unit 1

GTIN 4046356693936

Custom tariff number 85369010

Dimensions

Length [l] 12 mm

Pitch 3.5 mm

Dimension a 3.5 mm

Width [w] 8.5 mm

Height 13.1 mm

Height [h] 16.7 mm

Solder pin [P] 3.6 mm

Pin spacing 3.5 mm

Hole diameter 1 mm

General

Range of articles PTSA 1,5

Rated surge voltage (III/3) 2.5 kV

Rated surge voltage (III/2) 2.5 kV

Rated surge voltage (II/2) 2.5 kV

Rated voltage (III/3) 200 V

Rated voltage (III/2) 250 V

Rated voltage (II/2) 400 V

Connection in acc. with standard EN-VDE

Nominal current IN 8 A

Nominal cross section 1.5 mm²

Solder pin surface

Stripping length 9 mm

Number of positions 2

Connection data

Conductor cross section AWG min. 24

Conductor cross section AWG max. 16

Standards and Regulations

Connection in acc. with standard EN-VDE

Environmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

Classifications

eCl@ss 4.0272607xeCl@ss 4.127141109eCl@ss 5.027141190eCl@ss 5.127261100eCl@ss 6.027261100eCl@ss
7.027440401eCl@ss 8.027440401eCl@ss 9.027440401

ETIM 3.0EC001121ETIM 4.0EC002643ETIM 5.0EC002643ETIM 6.0EC002643

UNSPSC 6.0130211801UNSPSC 7.090139121432UNSPSC 1134131203UNSPSC 12.0139121432UNSPSC
13.239121432

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PTSA 1,5/ 2-3,5-ZI BK/GN with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.