INDUSTRIAL COMPONENT DATA

BP 4-4CT 3208723 PHOENIX CONTACT Short-circuit connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: BP 4-4CT



Manufacturer	PHOENIX CONTACT
MPN / Reference	BP 4-4CT
Catalog number	3208723
Category	Test plug for terminal blocks
Minimum order	10 Pcs
Document ID	EO-FF304A277A
Generated	2026-11-19

Product Overview

Short-circuit connector
Connector for four current transformers, each with a forward transformer short circuit

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Enclosures connectivity

Additional Product Information

Key Commercial Data
Orderkey 3208723
Packing unit 10 pc
Minimum order quantity 10 pc
Note Made to Order (non-returnable)
GTIN 4055626437552
Weight per Piece (excluding packing) 109.980 g
Custom tariff number 85366990
Country of origin PL (Poland)
General
Number of positions 8
Number of levels 1
Number of connections 8
Potentials 8

Nominal cross section 4 mm²
Color gray
Insulating material PA
Flammability rating according to UL 94 V0
Rated surge voltage 4 kV
Degree of pollution 3
Overvoltage category III
Insulating material group I
Maximum power dissipation for nominal condition 1.02 W
Ambient temperature (operation) -50 °C ... 100 °C
Ambient temperature (assembly) -40 °C ... 100 °C
Maximum load current 30 A
Nominal current IN 15 A
Nominal voltage UN 320 V
Open side panel No
Dimensions
Width 74.4 mm
Length 40 mm
Height 57.3 mm
Pitch 6.1 mm
Connection data
Connection method Bolt connection
Screw thread M4
Stripping length 8 mm ... 9 mm
Tightening torque, min 1.2 Nm
Tightening torque max 1.5 Nm
Connection in acc. with standard IEC 61984
Conductor cross section solid min. 0.5 mm²
Conductor cross section solid max. 2.5 mm²
Conductor cross section AWG min. 20
Conductor cross section AWG max. 14
Conductor cross section flexible min. 0.5 mm²
Conductor cross section flexible max. 2.5 mm²
Min. AWG conductor cross section, flexible 20
Max. AWG conductor cross section, flexible 14
Conductor cross section flexible, with ferrule with plastic sleeve min. 0.5 mm²
Conductor cross section fle...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / BP 4-4CT with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.