INDUSTRIAL COMPONENT DATA

PTTB 2,5-2DIO/O-UL/O-UR BK 3211444 PHOENIX CONTACT Component terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: PTTB 2,5-2DIO/O-UL/O-UR BK



Manufacturer	PHOENIX CONTACT
MPN / Reference	PTTB 2,5-2DIO/O-UL/O-UR BK
Catalog number	3211444
Category	Component terminal block
Minimum order	50 Pcs
Document ID	EO-6665E5E5AD
Generated	2026-11-18

Product Overview

Component terminal block
Terminal block for components, with integrated diode 1N4007, nominal voltage: 500 V, nominal current: 0.5 A, number of connections: 4, connection type: Push-in connection, 1st and 2nd floor, Dimensioning section: 2.5 mm², cross-section: 0.14 mm² - 4 mm², mounting class: NS 35/7.5, NS 35/15, color: black

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Modular TBs

Additional Product Information

Key Commercial Data
Orderkey 3211444
Packing unit 50 pc
Minimum order quantity 50 pc
Note Made to Order (non-returnable)
Catalog page Page 122 (C-3-2015)
GTIN 4055626348742
Weight per Piece (excluding packing) 12.610 g
Custom tariff number 85369010
Country of origin PL (Poland)
General
Note The max. current is determined by the diode. Installed: Diode 1N 4007, reverse voltage: 1300 V, maximum continuous

current: 0.5 A.
Number of levels 2
Number of connections 4
Nominal cross section 2.5 mm²
Color black
Insulating material PA
Flammability rating according to UL 94 V0
Rated surge voltage 6 kV
Degree of pollution 3
Overvoltage category III
Insulating material group I
Maximum power dissipation for nominal condition 0.77 W (the value is multiplied when connecting multiple levels)
Nominal current IN 0.5 A
Maximum load current 0.5 A (with 4 mm² conductor cross section)
Nominal voltage UN 500 V
Open side panel Yes
Relative insulation material temperature index (Elec.; UL 746 B) 130 °C
Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21)) 130 °C
Static insulating material application in cold -60 °C
Behavior in fire for rail vehicles (DIN 5510-2) Test passed
Flame test method (DIN EN 60695-11-10) V0
Oxygen index (DIN EN ISO 4589-2) >32 %
NF F16-101, NF F10-102 Class I 2
NF F16-101, NF F10-102 Class F 2
Surface flammability NFPA 130 (ASTM E 162) passed
Specific optical density of smoke NFPA 130 (ASTM E 662) passed
Smoke gas toxicity NFPA 130 (SMP 800C) passed
Calorime...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PTTB 2,5-2DIO/O-UL/O-UR BK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.