INDUSTRIAL COMPONENT DATA

# PTV 2,5-TWIN BK 1291495 PHOENIX CONTACT Feed-through terminal, nominal voltage: 800 V, nominal current: 24 A..

**Brand: PHOENIX CONTACT | Manufacturer Part Number: PTV 2,5-TWIN BK**

PRODUCT IMAGE\nNOT AVAILABLE

| | |
|---|---|
| Manufacturer | PHOENIX CONTACT |
| MPN / Reference | PTV 2,5-TWIN BK |
| Catalog number | 1291495 |
| Category | Feed-through terminal block |
| Minimum order | 100 Pcs |
| Document ID | EO-DAAF114488 |
| Generated | 2026-11-18 |

## Product Overview

Feed-through terminal, nominal voltage: 800 V, nominal current: 24 A, number of connections: 3, connection type: Push-in connection, Dimensioning cross-section: 2.5 mm2, cross-section: 0.14 mm2 - 4 mm2, mounting class: NS 35/7.5, NS 35/15, colour: black

Step terminal, rated voltage: 800 V, rated current: 24 A, connection type: Push-in connection, Sizing section: 2.5 mm², section: 0.14 mm² - 4 mm², mounting class: NS 35/7.5, NS 35/15, color: black

STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

| | |
|---|---|
| Catalog path | PHOENIX CONTACT > Modular TBs |

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PTV 2,5-TWIN BK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.