INDUSTRIAL COMPONENT DATA

# PTVFIX 18X2,5 GN 1019580 PHOENIX CONTACT Distribution block, rated voltage: 450 V, rated current: 24 A, numb..

**Brand: PHOENIX CONTACT | Manufacturer Part Number: PTVFIX 18X2,5 GN**

PRODUCT IMAGE\nNOT AVAILABLE

| | |
|---|---|
| Manufacturer | PHOENIX CONTACT |
| MPN / Reference | PTVFIX 18X2,5 GN |
| Catalog number | 1019580 |
| Category | Feed-through terminal block |
| Minimum order | 10 Pcs |
| Document ID | EO-B7C1C6476F |
| Generated | 2026-11-19 |

## Product Overview

Distribution block, rated voltage: 450 V, rated current: 24 A, number of connections: 18, number of poles: 1, connection type: Push-in connection, Sizing cross-section: 2.5 mm², cross-section: 0.14 mm² - 4 mm², mounting type: interlock in rail adapter, Direct mounting with a flange, Aerial, color: green
Distribution block, nominal voltage: 450 V, rated current: 24 A, connection type: Push-in connection, Dimensioning section: 2.5 mm², section: 0.14 mm² - 4 mm², mounting class: nail to rail adapter, Direct mounting with a flange, Aerial, color: green

STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

| | |
|---|---|
| Catalog path | PHOENIX CONTACT > FIX block System |

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PTVFIX 18X2,5 GN with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

**GLOBAL OFFICES**
Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.