INDUSTRIAL COMPONENT DATA

PTVFIX 2,5-3L/N/GNYE 1300613 PHOENIX CONTACT Device terminal, rated voltage: 690 V, rated current: 24 A, num..

Brand: PHOENIX CONTACT | Manufacturer Part Number: PTVFIX 2,5-3L/N/GNYE

PRODUCT IMAGE\nNOT AVAILABLE

Manufacturer	PHOENIX CONTACT
MPN / Reference	PTVFIX 2,5-3L/N/GNYE
Catalog number	1300613
Category	Feed-through terminal block
Minimum order	10 Pcs
Document ID	EO-ED06D08342
Generated	2026-11-18

Product Overview

Device terminal, rated voltage: 690 V, rated current: 24 A, number of connections: 10, number of poles: 5, connection type: Push-in connection, Sizing cross-section: 2.5 mm², cross-section: 0.14 mm² - 4 mm², Push-in connection, mounting type: interlock in rail adapter, Direct mounting with a flange, Aerial, color: gray/blue/green-yellow
Block for distribution

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > FIX block System

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PTVFIX 2,5-3L/N/GNYE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES
Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.