INDUSTRIAL COMPONENT DATA

PTVFIX 2X2,5 GN 1019466 PHOENIX CONTACT Monobloc, rated voltage: 450 V, rated current: 24 A, number of conne..

Brand: PHOENIX CONTACT | Manufacturer Part Number: PTVFIX 2X2,5 GN

PRODUCT IMAGE\nNOT AVAILABLE

Manufacturer	PHOENIX CONTACT
MPN / Reference	PTVFIX 2X2,5 GN
Catalog number	1019466
Category	Feed-through terminal block
Minimum order	30 Pcs
Document ID	EO-1BDF50DB8F
Generated	2026-11-18

Product Overview

Monobloc, rated voltage: 450 V, rated current: 24 A, number of connections: 2, number of poles: 1, connection type: Push-in connection, Sizing cross-section: 2.5 mm², cross-section: 0.14 mm² - 4 mm², mounting class: interlock in rail adapter, Direct mounting with a flange, Aerial, color: green
Block for distribution

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > FIX block System

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PTVFIX 2X2,5 GN with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES
Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.