INDUSTRIAL COMPONENT DATA

PTVFIX 6/18X2,5-NS35A RD 1019560 PHOENIX CONTACT Distribution block, nominal voltage: 690 V, nominal current..

Brand: PHOENIX CONTACT | Manufacturer Part Number: PTVFIX 6/18X2,5-NS35A RD

PRODUCT IMAGE\nNOT AVAILABLE

Manufacturer	PHOENIX CONTACT
MPN / Reference	PTVFIX 6/18X2,5-NS35A RD
Catalog number	1019560
Category	Feed-through terminal block
Minimum order	10 Pcs
Document ID	EO-7C7420EA5F
Generated	2026-11-19

Product Overview

Distribution block, nominal voltage: 690 V, nominal current: 24 A, number of connections: 19, number of poles: 1, connection type: Push-in connection, Branch, Dimensioning cross-section: 2.5 mm², cross-section: 0.14 mm² - 4 mm², Collective connection, Dimensioning cross-section: 6 mm², cross-section: 0.5 mm² - 10 mm², mounting class: NS 35/7.5, NS 35/15, colour: red
Distribution block, rated voltage: 690 V, rated current: 24 A, connection type: Push-in connection, Bypass, Sizing section: 2.5 mm², section: 0.14 mm² - 4 mm², Collective connection, Dimensioning section: 6 mm², section: 0.5 mm² - 10 mm², mounting class: NS 35/7.5, NS 35/15, color: red

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > FIX block System

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PTVFIX 6/18X2,5-NS35A RD with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.