INDUSTRIAL COMPONENT DATA

PV-14P1N22HG00 1592501 PHOENIX CONTACT Device connector, rear mounting

Brand: PHOENIX CONTACT | Manufacturer Part Number: PV-14P1N22HG00



Manufacturer	PHOENIX CONTACT
MPN / Reference	PV-14P1N22HG00
Catalog number	1592501
Category	Circular connector, mounting (without cable)
Minimum order	1 Pcs
Document ID	EO-15568D7FC4
Generated	2026-11-19

Product Overview

Device connector, rear mounting
Conect. plug. to be apar. poster wall, straight, Screw lock, M16, number of poles: 14, contact type: Male, Axial O-ring, Central fixing, shielded: no, protection index: IP67, number of poles: 14, connection type: Solder connection, series: PV

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Key Commercial Data
Orderkey 1592501
Packing unit 12 pc
Note Made to Order (non-returnable)
GTIN 4046356191357
Weight per Piece (excluding packing) 26.570 g
Custom tariff number 85366990
Country of origin DE (Germany)
General
Type of locking Screw locking
Insertion/withdrawal cycles mechanical 50
Coding N
Contact connection method Solder-in connection

Type of contacts Pin
Number of positions 14
Nominal current per power contact at 25°C 800 mA
Pg housing screw connection none
Mounting type Central fixing
Ambient conditions
Ambient temperature -20 °C ... 125 °C
Degree of protection IP67
Material
Housing material Turned parts: copper zinc alloy (CuZn), die-cast parts: zinc (GD-Zn)
Insulator material PA 6.6
Contact material CuZn
Contact surface Nickel-plated, gold coating
Gasket and O-ring material FPM
Specifications according to DIN EN 61984:2001
Installation height max. 2000 m
Nominal / operating voltage of power contacts 100 V
Rated surge voltage of power contacts 0.8 kV
Overvoltage category of power contacts II
Degree of pollution of power contacts 3
Overvoltage category of signal contacts II
Degree of pollution of signal contacts 3
Environmental Product Compliance
REACh SVHC Lead 7439-92-1
China RoHS Environmentally Friendly Use Period = 50
For details about hazardous substances go to tab “Downloads”, Category “Manufacturer's declaration”
Classifications
eCl@ss 4.0272607xxeCl@ss 4.127260701eCl@ss 5.027143424eCl@ss 5.127143400eCl@ss 6.027279200eCl@ss 7.027440103eCl@ss 8.0274...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PV-14P1N22HG00 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.