INDUSTRIAL COMPONENT DATA

PV-FT-C2F-C-2,5-75-BU-FLC 1463064 PHOENIX CONTACT Photovoltaic connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: PV-FT-C2F-C-2,5-75-BU-FLC



Manufacturer	PHOENIX CONTACT
MPN / Reference	PV-FT-C2F-C-2,5-75-BU-FLC
Catalog number	1463064
Category	Sensor-actuator connector chassis
Minimum order	200 Pcs
Document ID	EO-718AD53768
Generated	2026-11-19

Product Overview

Photovoltaic connector
Photovoltaic plug-in connector

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Key Commercial Data
Orderkey 1463064
Packing unit 200 pc
Note Made to Order (non-returnable)
GTIN 4046356757393
Weight per Piece (excluding packing) 22.220 g
Custom tariff number 85359000
Country of origin DE (Germany)
Dimensions
Fixed cable length 75 mm
Ambient conditions
Degree of protection (when plugged in) IP66 / IP68 (2 m / 24 h)
Degree of protection (not plugged in) IP65
Ambient temperature (operation) -40 °C ... 85 °C

Ambient temperature (assembly) -25 °C ... 50 °C
General
Design Socket
Tightening torque nut 1.8 Nm ±0.1 Nm
Insertion force 45 N ±10 N
Disconnect force 250 N ±50 N
Pull-out force of cable >= disconnect force > 80 N
Rated voltage 1500 V
Rated current (2.5 mm²) 27 A
Rated current (4.0 mm²)
Rated current (6.0 mm²)
Nominal cross section 2.5 mm²
Protection class II
Material
Color black
Insulating material mPPE
Contact material Cu
Contact surface material Ag
Flammability rating according to UL 94 V0
Connection data
Connection method Crimp
Connection capacity 2.5 mm²
Contact resistance with connected conductor 0.45 m?
Cable type S01
Conductor
Outer sheath, material PE-X
External sheath, color blue
Standards and Regulations
Flammability rating according to UL 94 V0
Environmental Product Compliance
China RoHS Environmentally friendly use period: unlimited = EFUP-e
No hazardous substances above threshold values
Classifications
eCl@ss 4.027060306eCl@ss 4.127060306eCl@ss 5.027061801eCl@ss 5.127260700eCl@ss 6.027260700eCl@ss 7.027440102eCl@ss 8.027440102eCl@ss 9.0274...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PV-FT-C2F-C-2,5-75-BU-FLC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.