INDUSTRIAL COMPONENT DATA

PV-FT-C3M-C-2,5-4-VPE250 1196772 PHOENIX CONTACT Crimp contact, Article family: SUNCLIX, number of poles: 1,..

Brand: PHOENIX CONTACT | Manufacturer Part Number: PV-FT-C3M-C-2,5-4-VPE250



Manufacturer	PHOENIX CONTACT
MPN / Reference	PV-FT-C3M-C-2,5-4-VPE250
Catalog number	1196772
Category	Contact for industrial connectors
Minimum order	250 Pcs
Document ID	EO-F52784DE3A
Generated	2026-11-19

Product Overview

Crimp contact, Article family: SUNCLIX, number of poles: 1, min. conductor cross-section: 2.5 mm², max. conductor cross-section: 4 mm², rated current: 27 A, Connection type: Crimping, Contact connection type: Male
Crimp Contact, Item Family: Sunclix, Pole Number: 1, Min. Conductor Cross-Section: 2.5 mm², Max. Conductor Cross-Section: 4 mm², Rated Current: 27 A, Connection Type: Crimp, Contact Connection Type: Male

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Technical dataNotesSafety Indication
Safety Notes • WARNING: Serve only products in perfect condition. Products should be checked regularly for damage. Remove defective products immediately. Replace damaged products. It is not possible to repair them.
• WARNING: only qualified personnel specialized in electrical engineering can install and use the product, always taking into account the following safety indications. Specialized personnel must be familiar with the fundamentals of electrical engineering. You must be able to identify and avoid hazards. The corresponding symbol on the packaging indicates that personnel specialized in electrical engineering are required for installation and operation.
WARNING: Connectors should not be plugged in or unplugged under load. Failure to comply and improper use can result in property damage and personal injury.
• The products are suitable for the areas of application of the construction of electrical equipment, control systems and systems.
• Ready-made products may not be tampered with or opened in an unauthorized manner.

• Use only mating connectors that comply with the technical data of the specified standards (e.g. those indicated on the product accessories on the website on phoenixcontact.com/products).
• The user is responsible for using the product directly in conjunction with products from other manufacturers.
• With operating voltages > 50 V AC, electrically conductive connector housings must be grounded
• Check that the functio...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PV-FT-C3M-C-2,5-4-VPE250 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.