INDUSTRIAL COMPONENT DATA

VS-ASI-FC-PVC-UL-BK/1000 1404870 PHOENIX CONTACT Flat-ribbon conductor

Brand: PHOENIX CONTACT | Manufacturer Part Number: VS-ASI-FC-PVC-UL-BK/1000



Manufacturer	PHOENIX CONTACT
MPN / Reference	VS-ASI-FC-PVC-UL-BK/1000
Catalog number	1404870
Category	Data cable
Minimum order	1 Pcs
Document ID	EO-02EAFFC28C
Generated	2026-11-19

Product Overview

Flat-ribbon conductor
AS-Interface PVC flat cable with UL in black, for additional power supply, 2 x 1.5 mm², 100 mm on disposable drum

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Key Commercial Data
Orderkey 1404870
Packing unit 1 pc
Note Made to Order (non-returnable)
Catalog page Page 438 (C-2-2017)
GTIN 4046356327602
Weight per Piece (excluding packing) 222.220 g
Custom tariff number 85444995
Country of origin DE (Germany)
Mechanical characteristics
Number of positions 2
Shielded no
Type of cable Flat-ribbon conductor
Cable structure 2x 1.5 mm²

Length of cable 1000 m
Ambient conditions
Ambient temperature (operation) -30 °C ... 90 °C (fixed routing)
-20 °C ... 90 °C (Flexibly installed)
Ambient temperature (assembly) -20 °C ... 90 °C
Ambient temperature (storage/transport) -30 °C ... 90 °C
Material data
Outer sheath, material PVC
External sheath, color black RAL 9005
Height 4 mm
Electrical characteristics
Rated voltage (III/3) 300 V
Rated surge voltage 2 kV
Line characteristics
Type of cable Flat-ribbon conductor
Cable structure 2x 1.5 mm²
Conductor cross section 1.5 mm²
AWG power supply 16
Conductor structure, voltage supply 84x 0.15 mm
Core diameter including insulation 2.5 mm
Thickness, insulation approx. 0.5 mm
Wire colors brown, blue
External sheath, color black RAL 9005
Insulation resistance >= 1 M?*km
Conductor resistance <= 13.7 ?/km
Nominal voltage, cable 300 V
Test voltage, cable 2000 V
Outer sheath, material PVC
Material conductor insulation TPE
Conductor material Bare Cu litz wires
Cable weight 73 kg/km
Smallest bending radius, fixed installation >= 6 mm (one-time)
Traversing direction horizontal, above the broadside
Max. bending cycles 8...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / VS-ASI-FC-PVC-UL-BK/1000 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.