INDUSTRIAL COMPONENT DATA

Q 0,75/3A50/9-9KU-ESA BK 1642072 PHOENIX CONTACT Panel feed-through

Brand: PHOENIX CONTACT | Manufacturer Part Number: Q 0,75/3A50/9-9KU-ESA BK



Manufacturer	PHOENIX CONTACT
MPN / Reference	Q 0,75/3A50/9-9KU-ESA BK
Catalog number	1642072
Category	Sensor-actuator connector chassis
Minimum order	10 Pcs
Document ID	EO-49B8B391D9
Generated	2026-11-19

Product Overview

Panel feed-through

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > QUICKON Installation System (QPD)

Additional Product Information

Key Commercial Data
Orderkey 1642072
Packing unit 10 pc
Minimum order quantity 10 pc
Note Made to Order (non-returnable)
GTIN 4017918895570
Weight per Piece (excluding packing) 33.180 g
Custom tariff number 85369010
Country of origin PL (Poland)
General
Connection If the conductor is reconnected, it must be cut off above the last contact point. QUICKON components may only be operated when under no load.
Length of cable 0.5 m
Color black
Connection method QUICKON connection

Single litz wires 50 cm long; 0.75 mm²
Note on the internal connection method Pos. 1: Brown; pos. 2: White; pos. 3: Blue
Number of positions 3
Wrench size, union nut 19 mm
Tightening torque, union nut 2.5 Nm
Wrench size, contact carrier 19 mm
Tightening torque contact carrier 3.75 Nm
Tightening torque, counter nut 3.75 Nm
Conductor cross section flexible min. 0.34 mm²
Conductor cross section flexible max. 0.75 mm²
Cabel
Structure of individual litz in acc. with VDE 0295 / smallest wire diameter Class 2-6 // 0.34 mm²: 0.1 mm; 0.5 - 0.75 mm²: 0.15 mm
Wire insulation material PVC / PE
Wire diameter including insulation 2.5 mm
Ambient conditions
Degree of protection IP65
IP67
Ambient temperature (operation) -25 °C ... 80 °C (Specifications of the cable manufacturer must be observed.)
-25 °C ... 50 °C (when the conductor is connected. Specifications of the cable manufacturer must also be observed.)
Electrical characteristics
Nominal current IN 9 A
Rated voltage (III/3) 160 V
Note on the rated voltage (III/3) wi...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / Q 0,75/3A50/9-9KU-ESA BK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.